

Through -Parivesh Portal



दूर की सोचं 31st May, 2025

Ref: PJL/MIN/BDR/2025/36

To,
Regional Director
Ministry of Environment & Forests and Climate Change
Regional Office, Western Region,
Kendriya Paryavaran Bhavan,
Link Road No. 3, E - 5, Ravi Shankar Nagar,
Bhopal – 462016

Subject: - Submission of Six-Monthly Compliance Report for Environmental Clearance Bandarkha Limestone Mine (40.236 ha), M/s Prism Johnson Ltd., Village Bandarkha, Tehsil Rampur Baghelan, District Satna, Madhya Pradesh

Reference: Environmental Clearance Letter No. 3080/SEIAA/13, dated 20th March 2013.

Dear Sir,

With reference to the above subject and the Environmental Clearance granted vide your letter no. 3080/SEIAA/13, dated 20th March 2013, we hereby submit the six-monthly compliance report for the period October 2024 to March 2024 for the Bandarkha Limestone Mine located at Village Bandarkha, Tehsil Rampur Baghelan, District Satna, Madhya Pradesh.

The compliance report has been prepared in accordance with the stipulated conditions of the environmental clearance, and all relevant supporting documents are enclosed for your kind perusal.

We trust that the report meets the required standards and is in order.

Thanking you.

Yours sincerely,

For Prism Johnson Limited


DOWN'

Chandra Shekhar Pandit

Sr. GM-Mines & Project Proponent

Enclosures: As stated above









COMPLIANCE OF CONDITIONS AS STIPULATED BY MoEF LETTER VIDE NO. 3080/SEIAA/13, DATED 20.03.2013, LIMESTONE DEPOSIT OVER 40.236 HECT. AREA IN VILLAGE BANDARAKHA, TEHSIL RAMPUR BAGHELAN, DIST. SATNA (M.P.)

A. Spe	ecific Conditions :-	
	Conditions	Compliance status
1.	If the land belongs to the tribal person the Collector shall ensure that the tribal person gets compensation as per rule 72 of the Mineral Concession Rule 1960 and his interests are safeguarded as per State policy.	The land of the core area is devoid of any tribal person, therefore not applicable.
2.	Controlled blasting will be done as per guidelines of IBM; delay detonating technique will be adopted and down hole initiation system will be adopted.	Controlled blasting is being practiced using delay detonators and down the hole initiation system.
3.	All pollution control devices will be installed as per guidelines of CPCB/MPPCB.	Air, Noise & Water Quality is monitored regularly and found within the permissible limit. Ambient Air quality and Noise quality data attached as Annexure- 1
4.	Appropriate measures to control the silt shall be taken and reported to avoid the possible disturbance of aquatic eco system of river Tamas.	Garland drain and siltation pond have been constructed to arrest the silt and sediment flow. Garland drain having width of 2.0 to 3 meters and depth of 0.75 to 1.2 meter already constructed.
5.	Dense plantation all along the transportation road has to be taken up immediately	Extensive plantation is being done along the road. Cumulative plantation is 9210 planted on 4.25 ha area.
6.	Mine wise production record shall be maintained at site.	Mine production is being maintained. Mining is being carried out as per approved Mining Plan.
7.	The water reservoir as proposed in 21.12 ha shall be fenced and aesthetically developed.	Water reservoir Will be developed as per approved mining plan and scheme of mining by IBM. Fencing has also been done around mine boundary.
8.	Afforestation on 17 Ha area with minimum 17,020 numbers of trees as proposed shall be taken up with mining.	Plantation has been done in phase manner annually. Total 9210 plants have been planted on 4.25 ha area maintaining the plantation density as per the condition. In addition to that 30,000 no.s of substitute plantation on 14 acre
		area has been done at Satari village.

B. GE	ENERAL CONDITIONS:-				
	Conditions		Compliance status		
1.	Any addition of mining area, change of Khasra numbers, enhancement of capacity, change in mining technology, modernization and scope of working shall again require prior environment clearance as per EIA notification, 2006.	No changes have been made. Will be complied any change is proposed.			
2.	All activities / mitigate measures proposed by PP in Environmental Impact Assessment and approved by SEAC must be ensured.		es of mitigation measures are taken by us as oposed plan and are mentioned below:		
			Mitigation Measures as per REIA		
		1	Wet Drilling or dry drilling with in-built cyclone and bag filter arrangement is being deployed.		
		2	Water is sprayed on haul roads using water tanker.		
		3	Maintenance and PUC of vehicles is done regularly to prevent air pollution, smoke and gaseous pollution.		
		4	Teeth of shovel are kept sharpened to avoid dust emission.		
		5	Plantation is done in phase manner to prevent dust, smoke etc.		
		7	Plantation is done on dumps for slope stabilization.		
		8	Controlled blasting with down the hole initiation is adopted which produces less noise, vibration and better fragmentation.		
		9	NONEL system of initiation is followed to minimize noise.		
		10	No. of blast holes per day are kept to a minimum.		
		11	PPEs are distributed to workers for their safety.		
		12	Appropriate subgrade drilling is being followed.		
		13	Pattern blasting is being practiced which produces less noise and vibration.		
		14	Physical barriers such as bunds/embankment and green belt are developed to prevent noise from going outside.		
		15	Garland drains and siltation tank have been constructed to prevent water pollution and in-rush of water.		

		16	Water is discharged/stored into adjoining
			pit after treatment with the settling pond.
		17	Extensive plantation is being carried out
			around the lease periphery and Tamas
			River side to prevent air and noise
			pollution.
		18	Limestone and Overburden is properly
			handled to prevent dust emission and its
			impact on nearby flora and fauna.
		19	There is a school in colony in which
			children of employees and villagers
			study.
		20	A well-equipped dispensary has been
			provided with 3 full time medical officers
			assisted by adequate paramedical staff,
			for the local villagers. Also, a mobile
			clinic van along with a doctor and
			paramedical staff makes regular visits to
			the nearby villages and provided free
			medical advice and medicines to the
			local habitants.
		21	A two lane WBM road has been
			constructed by the lessee connecting the
			national highway-39 with Sljahtta village
			via Mankahari and Bamhauri village.
		22	Aid is provided to the needy in the
			villages in the form of scholarships.
			Donations for conducting sports have
			been given.
3.	All activities / mitigate measures proposed		
J.	by PP in Environmental Management Plan		pes of mitigate measures are taken by us as
	and approved by SEAC must be ensured.	per pr	oposed plan and are mentioned below:
			Mitigation Measures as per EMP
		Air E	Invironment
		1 1	Haulage of overburden to the proposed
			dumps siding and that of limestone to the
			crusher is being done by dumpers. Water
			spraying is used as part of mitigation
			measures. No local roads are being used,
			still they are have been converted to WBM
			roads which are maintained regularly.
		2	Plantation along the approach road is done
		1	to reduce spread of dust.
		3 1	Dust masks and other PPEs are provided
Ì		i I — I	
		1	to workers and it is compulsory to wear
			to workers and it is compulsory to wear them in dusty atmosphere.
		1	• • •

	to prevent vehicular emissions.
5	Regular monitoring of air quality is done.
Noi	se Environment
1	Green belt development is in progress and the same will be continued in phased manner.
2	A major portion of the transportation comes under mine lease area with 200 n minimum distance between the lease and village. Trees are being planted on both sides of the approach roads.
3	Regular maintenance and lubrication of machineries is done.
4	PPEs like ear plugs are provided to the workers and employees.
5	Controlled blasting with muffles are used to minimize noise.
Wa	ter Environment
1	To reduce suspended solids, coming to mine pits, garland drains are being constructed at around the pit and around the dumps also. All garland drains are connected to the settling tank and the water is being used for dust suppression.
2	Mine has started its production. The Sumphas been developed at the bottom of the pit. A siltation pond has already been constructed at the earmarked location.
3	Garland drains are regularly de-silted.
	nd Environment and Solid Waste
Maı	nagement
1	Dumps are stabilized by plantation of slopes.
2	Plantation has been done in phase manne annually. Total 9210 plants have been planted on 4.25 ha area maintaining the plantation density as per the condition.
	30,000 no.s of substitute plantation on 14 acre area has been done at Satari village.
	logical Environment
Bio	logical Elivinolinion

		It has been observed that the species forms dense canopy once grown.
		All the species planted are local species.
4.	All parameters listed in Environmental Monitoring Plan approved by SEAC must be monitored at approved locations and frequencies.	Monitoring is being done at designated locations and analysis report is being submitted to MPPCB on monthly basis.
5.	Blast vibration study shall be conducted and submitted to the Regional Office, MoEF, Gol, Bhopal and MP PCB within six months. The study shall also provide measures for prevention of blasting associated impact on nearby houses and agricultural fields.	The Blast vibration study has been conducted by AKS University Satna. The recommended blast designs in the report are being followed for day-to-day blasting operations for safe and efficient blasting operations. The copy of the same is attached as Annexure-2
6.	Controlled blasting techniques with sequential drilling shall be adopted. The blasting shall be carried out in the day time only.	We practice controlled blasting using Non electric delay detonators (Nonel), limiting charge per delay and blast size. Moreover, periodical blasting study is conducted by scientific bodies, like AKS University, to evaluate and establish the safe practice of blasting so as to eliminate/minimize any adverse impact of blasting in nearby surrounding area.
		All the suggestion and finding of study are implemented and all the provisions of applicable statutes and all directions/guidelines of approving authorities, like DGMS, IBM are strictly followed.
7.	Slope of mining bench and ultimate pit limit shall be as per the mining scheme approved by Indian Bureau of Mines.	Mining benches and ultimate pit limit shall be maintained as per mining scheme approved by Indian Bureau of Mines for ensuing period.
8.	A final mine closure plan, along with details of Corpus Fund, shall be submitted to the Regional Office, MoEF, Gol, Bhopal and MPPCB within 5 years in advance of final mine closure for approval.	Agreed. We will Submit as per stipulation.
9.	No change in calendar plan including excavation, quantum of mineral and waste	No changes have been made.

	shall be made.	Figu	res of lime	estone prod	duction to be	e furnished.			
			Production Plan for last Six years for 40.236 ha.						
		SI no.	FY	Productio n plan as per SoM	Production as per EC limit	Actual production	limits.		
		1.	2019-20	240000	240000	143684	EC		
		2.	2020-21	240003	240000	239923	.ihi		
		3.	2021-22	500000	240000	239685	, M		
		4.	2022-23	500013	240000	239390	tiol		
		5.	2023-24	500000	240000	229924	Production within		
		6	2024-25	505953	240000	210297	Pro		
10.	Mining will be carried out as per the approved mining plan. In case of any violation of mining plan, the Environmental clearance given by SEIAA will be stand cancelled.		ng is beir ng plan by	-	out as per	the appro	ved		
11.	Adequate buffer zone shall be maintained between two consecutive mineral bearing deposits.	The	•		mineral d	leposit her	ice,		
12.	The transportation of the minerals extracted from the mining area shall be limited to day hour time only.		stone Mir s only.	neral is stri	ctly transpoi	rted during	day		
13.	Maintenance of nearby local roads through which transportation of minerals are undertaken shall be carried out by company regularly at its own expenses. The roads shall be blacked topped.	All transportation is through internal roads which are motorable, rehabilitated with stone chips and stone dust on regular basis. No local roads are being used for mineral transportation and, the roads are maintained regularly.							
14.	Measures of prevention and control of soil erosion and management of slit shall be undertaken. Protection of dumps against erosion shall be carried out with geo textile matting or other suitable mineral and thick plantations of native trees and shrubs shall be carried out at the dump slopes. Dumps shall be protected by retaining walls.	Soil and waste dumps are stacked as per approved scheme of mining and are protected from erosion by carrying out suitable plantation, construction of toe drains and retaining wall. Also, no permanent dumps are present and temporary dumps will be used for backfilling.					sion n of ent		

Trenches/garland drains with settling pond is being Trenches/garland drains shall be constructed at foot of dumps and these drains constructed at foot of dumps and coco connect to settling pond which is de-silted at filters installed at regular intervals to arrest regular intervals. slit from being carried to water bodies. There is no water body, streams exist within the Adequate number of check dams and gully ML area neither seasonal nor perennial. The water shall be constructed plugs discharge from the mine is nil. Siltation pond has seasonal/perennial Nallahs, if any, flowing been constructed to arrest the silt. through the ML area and silts arrested. De-silting at regular intervals shall be carried out. The Proper berms garland drains and fencing are will project proponent ensure necessary protection measures around the constructed around mine pit area and garland mine pit, waste dumps and garland drain. drains with retaining wall have been provided. Top soil / solid waste shall be stacked Top soil/ solid waste generated during mining is properly with proper slope and adequate stacked separately & its being used for reclamation

Top soil / solid waste shall be stacked properly with proper slope and adequate safeguards and shall be utilized for backfilling (where ever applicable) for reclamation and rehabilitation of mined out area. Top soil shall be separately stacked for utilization later for reclamation and shall

stacked separately & its being used for reclamation of mined out area by spreading it over the waste rock after backfilling. Dumps are maintained as per mine plan. Dumps are temporary. The top soil is being used for greenbelt development. The stored soil will also used for plantation in barrier zones

	not be stacked along with over burden.	and over backfilled area to be developed in future.
18.	Over burden(OB)shall be stacked at earmarked dumpsite(s) only and shall not be kept active for long period., The maximum height of dump shall not exceed 20m, each stage shall preferably be of maximum 10 m and overall slope of the dump shall not exceed 35°. The OB dump shall be backfilled and shall be scientifically vegetated with suitable native species to prevent erosion and surface run off.	The Overburden generated during mining has been stacked at earmarked dump site only and is being stacked in 1 or 2 stages, height of each stack not exceeding 10m and slope not exceeding 35°. The dumps shall be backfilled as approved mine plan by IBM. Plantation is being done on dumps for slope stabilization and to prevent surface runoff.
19.	Minimum 1000 plants shall be planted in one year and 5000 plants shall be planted in first five years.	Plantation has been done in phase manner annually. Total of 9210 plants have been planted on 4.25 ha area maintaining the plantation density as per the condition.
		30,000 nos of substitute plantation on 14 acre area has been done at Satri village.
20.	Monitoring and management of rehabilitated areas shall continue until the vegetation becomes self-sustaining. Compliance status shall be submitted to the Regional Office, MoEF, Gol, Bhopal and MP PCB on six monthly basis.	Requirement is/will being/be complied. The compliance report is/will being/be sent every six months to the Regional Office, MoEF, Gol, Bhopal and MPPCB.
21.	By the end of the lease period 33% of the area should be brought under plantation.	Out of 32.15 ha of broken area, 10.75 ha will be reclaimed and rehabilitated by way of backfilling and plantation at the end of life of the mines.
22.	Green belt development shall be carried out considering CPCB guidelines including selection of plant species and in consultation with local DFO/Agricultural Deptt. Herbs / shrubs shall also form a part of afforestation programme besides tree plantation. The company shall involve local people for plantation programme. Details of year wise afforestation programme including rehabilitation of mined out area shall be submitted to the Regional Office, MoEF, Gol, Bhopal and MP PCB every	Greenbelt is being developed in phased manner. All plants species are selected on recommendations of District Forest Officer and local villagers. The compliance reports are being sent every six months to the Regional Office, MoEF, Gol, Bhopal and MPPCB.

	year.	
23.	Vehicular emissions shall be kept under control and regularly monitored. Vehicles used for transportation of minerals and others shall have valid permissions as prescribed under Central Motor Vehicle Rules,1989 and its amendments. The vehicles transporting minerals shall be covered with a tarpaulin or other suitable enclosures so that no dust particles / fine matters escape during the course of transportation. No overloading of minerals for transportation shall be committed. The truck transporting minerals shall not pass through wild life sanctuary, if any in the study area.	Emission from the vehicles engaged in the mine is kept under control. A centralized workshop has been established. Regular maintenance of all vehicles is done as per manufacturer's maintenance schedule i.e. changing of timely diesel filters, calibration of Fuel pump, overhauling of engines etc. No vehicles without valid PUC area allowed to be deployed inside the plant and mines area. The vehicles engaged in transportation of minerals outside the core zone will be provided with tarpaulin and overloading is not allowed.
24.	For ambient air quality monitoring stations shall be established in core zone as well as in the buffer zone for RSPM,SPM,SO2,NOx monitoring. Location of the stations should be decided based on the meteorological data, topographical features and environmentally and ecologically sensitive targets and frequency of monitoring should be undertaken in consultation with State Pollution Control Board. The monitored data for criteria pollutants shall be regularly uploaded and displayed on the company's website.	Ambient air quality monitoring for the given parameters is being done as per the directions given and data generated is being uploaded on company website. Ambient air quality monitoring results have been given in Annexure-3 .
25.	Data on ambient air quality (RPM, SPM, SO2, and NOx) should be regularly submitted to the Regional Office, MoEF, Gol, Bhopal and state Pollution Control Board / Central pollution control Board once in six months.	Being done. The compliance reports are being sent every six months to the Regional Office, MoEF, Gol, Bhopal and MPPCB. Ambient air quality monitoring results have been given in Annexure-3 .
26.	Ambient air quality at the boundary of mine premises shall confirm to the norms prescribed in MoEF notification No. GSR/826(E) dtd. 16.11.09.	Being complied. All Air quality parameters monitored are within NAAQS standards. Ambient air quality monitoring results attached as Annexure-3 .
27.	Fugitive dust emissions from all sources shall be controlled. Water spraying arrangement on haul, roads, loading and unloading at transfer points shall be	Water sprinkling is being done on haul roads for dust suppression. Wet drilling is being practiced. Vehicle speed is limited below 20 km/hr. Regular monitoring of dust emission is being done through

NABL/ MoEFCC accredited laboratory. provided and properly maintained. The dust emission shall be monitored regularly emission norms are being complied and the report as per norms and records to be submitted is being submitted. to the Regional Office, MoEF, Gol, Bhopal The compliance report are being sent every six and MPPCB regularly. months to the Regional Office, MoEF, Gol, Bhopal and MPPCB. Ambient Noise level is monitored at designated 28. Measures shall be taken control of noise locations and report is being submitted to MPPCB level below 75dBA the work on monthly basis. Noise monitoring report have environment. Workers engaged in been given in Annexure- 4. operations of HEMM, etc. shall be All the workers engaged in mining activity shall be provided with ear plugs/muffs and health provided the PPEs including ear plugs and muffs records of workers shall be maintained. and health checkup is being done and records being maintained. Total PPE's for Mines From Oct'2024 - Mar'2025 Total Material Qty. **Amount Dust Mask** 175 2665.25 Google Safety Glass PVC. 65 3303.95 **Hand Gloves** 165 5643 **Helmet Industrial Safety** 60 6900 Jacket fluorescent High 195 24765 Visibility Wear Plug Ear muff 275 2200 Safety Shoes 350 356300 **TOTAL** 1285 401777.2 Rain water harvesting shall be undertaken Rainwater harvesting practices have been to recharge the ground water source. implemented. 12 Nos of rooftop rainwater harvesting system, 4 abandoned pits and 4 nos of Status of implementation shall be submitted to the Regional Office, MoEF, recharge pits have been constructed inside plant, Gol, Bhopal and MP PCB within six mines and township. months and thereafter every year from the Other than this, the company has taken various next consequent year. initiatives like, construction of water harvesting structures on wells, ponds, pond deepening, maintenance of check dams, perforated drum water harvesting structures. Regular monitoring of ground and surface 14 Piezometers have been constructed to monitor water sources for level and quality shall be ground level. Water level and quality is analyzed in carried out by establishing a network of Pre - Monsoon, Monsoon, Post Monsoon, and existing wells and constructing winter seasons. Report of monitoring is generated piezometers during the mining operation. and submitted to MoEF&CC Bhopal, MPPCB, and The monitoring shall be carried four times CGWA & CGWB. Groundwater quality report and

a year i.e. pre-monsoon (April-May) level is attached is **Annexure-5** Post ,Monsoon (August), monsoon Since the mine working is restricted above the (November) and winter(January) and the ground water table, there is no chance of data thus collected shall be regularly sent contamination of ground water. to the Regional Office, MoEF, Gol, Bhopal and MP PCB ,Central Ground Water Authority and Regional Director, Central Ground Water Board. The waste water from the mine if any shall Not Applicable. be treated to confirm to the standards No workshop in lease area, we have a common prescribed under GSR 422(E) dated 19th workshop for all leases with appropriate May, 1993 and 31st December, 1993 or as arrangements. amended from time to time. The oil and grease trap shall be installed for the effluents generated from the workshop, if any, before discharging into the natural stream. The discharged water from tailing dam, if any shall be regularly monitored and report submitted to the Regional MoEF, Office. Gol. Bhopal, Central Pollution Control Board, and the State Pollution Control Board. Hydro-geological study of the area shall be The hydrogeological study of the area is reviewed reviewed by project proponent annually.In as required. case adverse effect on ground water Excavation of limestone is proposed up to only quality and quantity is observed mining 16m and currently we are working at a depth of shall be stopped and resumed only after 10m to 14m only. Water table will not be mitigating steps to contain any adverse intersected. impact on ground water is implemented. Regular monitoring of groundwater is carried out. Groundwater quality report is attached is Annexure- 5(A) Occupational health checkup for workers Periodical Medical Examinations are conducted for including identification of work related each employee by outside specialists once in every health hazards, training on malaria 5 years. Under this scheme each employee eradication, HIV, and health effects on undergoes Pathological tests, blood group test, exposure to mineral dust etc. shall be chest X-Rays, Audiometry tests, eye test etc. once carried out. Periodic monitoring for every 5 years. Proper records of such tests are maintained. exposure to respirable mineral dust on the workers shall be conducted and records All the workers engaged in mining activityis provided maintained including health records of the with the PPEs including ear plugs and muffs and workers. Awareness programme health checkup is being done and records workers on impact of mining on their being maintained. health and precautionary measures like Awareness training programs related to health and use of personal equipment etc. shall be safety is given to all workers at VT center. carried out periodically. Review of impact

	of various health measures shall be conducted followed by follow up action wherever required. It should be made available for inspection whenever asked. Necessary funds for this also should be earmarked.		The Report of the OHC is attached as Annexure 6 for reference.				
34.	Project proponent shall ensure appropriate arrangement for shelter and drinking water for the mine workers.	w	ppropriate arrangement rater is provided in the anine workers.		-		
35.	Person working in dusty areas shall be	Р	PE 's is provided to each	employees.			
	provided with protective respiratory devices and they shall also be imported adequate training and information on		espiratory devices are be orking in dusty areas.	eing used by	the persons		
	safety and health aspects.	Adequate training on Integrated Managemers system, safety and health awareness is be provided to workers frequently.					
		Р	PEs distribution details a	re as follows	:		
			Total PPE's for Mines Fro	om Oct'2024 –	Mar'2025		
			Material	Qty.	Total Amount		
			Dust Mask	175	2665.25		
			Google Safety Glass PVC.	65	3303.95		
			Hand Gloves	165	5643		
			Helmet Industrial Safety	60	6900		
			Jacket fluorescent High Visibility Wear	195	24765		
			Plug Ear muff	275	2200		
			Safety Shoes	350	356300		
			TOTAL	1285	401777.2		
36.	Commitment towards CSR has to be	В	eing followed.				
	followed strictly.	W V ei co	arious programs for relfare have been take arious social, educat nvironment initiatives having many. Drinking wa rovided; Construction of been done. Installation of rimary School, renoval havan has been done nedicines distribution from the control of the contro	n up by the ional, healt ave been to ter facility WBM roads, of new hand Governmention of Bale. Free commented the problem of the problem of the problem by the problem of the problem of the problem problem by the problem of the problem by the pro	e company. thcare and aken by the has been Toilets have pumps with t Middle & huuddeshiya hsultation & dical centre		

		eye Camp for cataract patients from nearby villages (20 Nos.). 24 hrs ambulance facility to nearby villagers—free of cost and many other activities—have been undertaken in CSR.CS—expenditure for the period Apr 24 - Sep 24—attached as Annexure-7 .							
37.	Special measures shall be adopted to prevent the nearby settlements from the impacts of mining activities.	to the 250m minin	There is no nearby settlement in the close vicinity to the mines. the nearest settlement is more than 250m away. All measures is being adopted while mining as per guidelines of MMR 1961 and Mines Act 1952 and as per the benefit of the community.						
38.	The project proponent shall inform to the to the Regional Office, MoEF, Gol, Bhopal and MP PCB regarding date of financial closures and final approval of the project by the concerned authorities and the date of start of land development work.	The intimation has been sent to MoEF Gol, Bhopal and MPPCB regarding date of financial closures and final approval of the project by the concerned authorities. Work has been started.							
39.	The necessary funds as per mandate shall kept for environmental protective measures which should be kept in separate account and shall not be diverted for other purpose. Year wise expenditure shall be reported to the Regional Office, MoEF, Gol, Bhopal and MP PCB.	Complying with the given condition, we have earmarked a fund for environmental protection equipment the fund will not diverted for any other purpose. The capital cost and recurring cost annum earmarked for environmental protection is given below: Year wise expenditure is being reported through							
		S. No.	Particulars	Proposed Capital cost	Proposed Annual recurring cost				
		1.	Pollution Control	4.19	0.23				
		2.	Pollution Monitoring	-	2				
		3.	Occupational Health & Safety	-	1.31				
		4.	Afforestation	-	1.4				
		5.	Reclamation / Rehabilitation of mined out area	0	3				

			Otho	ro / Fonsing		I				
		6.		rs (Fencing safety)	5.76	-				
		Environmental 7. Studies & Fees			0.8	0.44				
			T	otal	10.75	8.38				
						(in Lac Rupe	ees)			
40.	and MP PCB shall monitor compliance of the stipulated conditions. A complete set of documents including Environment impact Assessment Report, Environmental	sub reg the	mitted ularly a	to Six Mon to MoEFC and the same The referend low:	C, Bhopal is being m	and MPP onitored as p	CB per			
	Management Plan, public Hearing and other relevant documents should be given to the Regional Office, MoEF, Gol, Bhopal and MP PCB.		Year	Bandarkh	a Limestone M	ine				
			icai	Dispatcl	h no.	Date				
		-	2019	MIN/2019/	BDR/038	01.06.2019				
				MIN/2019- BDR/90		04.12.2019				
			2020	MIN/2020- E	3DR/0140	01.06.2020				
				MIN/2020- E	3DR/0169	02.12.2020				
			2021	MIN/2021-	BDR/087	01.06.2021				
			_		MIN/2021-	BDR/058	01.12.2021			
							2022	MIN/2022-	BDR/31	01.06.2022
				MIN/2022-	BDR/50	01.12.2022				
			2023	MIN/BDR/2	2023/22	01.06.2023				
				MIN/BDR/2	2023/37	01.12.2023				
		•	2024	MIN/BDR/2	2024/13	01.06.2024				
				MIN/BDR/2	2024/26	01.12.2024				
41.	A copy of the environmental clearance shall be submitted by the project proponent to the Heads of the local Bodies, Panchayat and Municipal Bodies, as applicable, in addition to the relevant officers of the Government who in turn has to display the same for 30 days from the date of receipt.	bee	en subr	the environme mitted to Pa aghelan. Atta	nchayat an	nd SDO Offi				
42.	The project proponent shall advertise at least in two local newspapers widely		•	News of acc		•				

	circulated, one of which shall be in the vernacular language of the locality concerned, within 7 days of the issue of the clearance letter informing that the project has been accorded environmental clearance and a copy of the clearance letter is available with the State Pollution Control Board and also at website of State Level Environment Impact Assessment Authority (SEIAA) website at and a copy of the same shall be forwarded to the Regional Office, MoEF, Gol, Bhopal.	att	ached as	s Annexure-9				
43.	The project proponent has to strictly follow directions/guideline issued by MoEF, Gol, CPCB and other Govt. agencies from time to time.	Ag	reed.					
44.	Action plan with respect to suggestion/ improvement and recommendations made and agreed during public hearing consultation shall be submitted to the regional Office, , MoEF, Gol, Bhopal and MP PCB and to the competent authority of state govt. within six months.	Complied. Status of suggestions and recommendations received during public hearing is enclosed as Annexure-10 .						
45.	yearly compliance report of the stipulated prior environmental clearance terms and	twi	The six monthly Compliance report is submitted twice every year. The reference letter nos are mentioned in table below:					
	conditions in hard and soft copy to the regulatory Authority on 1st June and 1st		Year	Bandarkha Limestone	Mine			
	December of each calendar year.		Teal	Dispatch no.	Date	_		
			2010	MIN/2019/ BDR/038	01.06.2019	_		
			2019	MIN/2019- BDR/90	04.12.2019	_		
			2020	MIN/2020- BDR/0140	01.06.2020			
			2020	MIN/2020- BDR/0169	02.12.2020	_		
			2021	MIN/2021- BDR/087	01.06.2021			
			2021	MIN/2021- BDR/058	01.12.2021			
			2022	MIN/2022-BDR/31	01.06.2022			
				MIN/2022-BDR/50	01.12.2022			
			2023	MIN/BDR/2023/22	01.06.2023			

2023

MIN/BDR/2023/37

01.12.2023

			2024	MIN/BDR/2024/13	01.06.2024
			2024	MIN/BDR/2024/26	01.12.2024
46.	The SEIAA of MP reserves the right to add additional safeguard measures subsequently, if found necessary and to take action including revoking of the environment clearance under the provisions of the environmental (protection) Act,1986,to ensure effective implementation of the suggested safeguard measures in a time bound and satisfactory manner.	Ag	reed.		
47.	These stipulations would be enforced among others under the provisions of water(Prevention and control of pollution) act,1974,the air(Prevention and control of pollution) Act 1981,the Environment(Protection) Act,1986 the public Liability (insurance) Act 1991 and EIA Notification,2006.	Ag	reed.		
48.	The Ministry or any other competent authority may alter/modify the conditions or stipulate any further condition in the interest of environment Protection.				
49.	Concealing factual data or submission of false/fabricated data and failure to comply with any of the conditions mentioned above may results In withdrawal of this clearance and attract action under the provisions of environment (protection) Act, 1986.	submission of false/fabricated data and failure to comply with any of the conditions mentioned above may results In withdrawal of this clearance and attract action under the provisions of environment			lata and failure to s mentioned above his clearance and
50.	Any appeal against this prior. Environmental Clearance shall lie with the green tribunal, If necessary, within a period of 30 days as prescribed under section 16 of the national Green tribunal Act, 2010.	Ag	reed.		
51.	All other statutory clearances such as the approvals for storage of diesel from chief controller of explosives, fire department, civil aviation department, Forest conservation act, 1980 and wildlife (protection) Act, 1972 etc. shall be obtained, as applicable by project	No	t applica	able.	

proponents from the respective component authorities.

52.

The proponent shall upload the status of compliances of stipulated EC conditions, including results of monitored data on their website and shall update the same periodically. It shall simultaneously be sent to the regional office of MoEF, the respective zonal office of CPCB and the SPCB. The criteria pollutant levels namely,SPM, RSPM,SO2, NOx (ambient levels as well as stack emissions) or critical sectoral parameters, indicated for the projected shall be monitored and displayed at a convenient location near the main gate of the company In the public domain.

The six-monthly EC compliance report is being uploaded on company website.

The six monthly Compliance report is submitted twice every year to the regional office of MoEF, the respective zonal office of CPCB and the SPCB.. The reference letter nos are mentioned in table below:

Year	Bandarkha Limestone	Mine
	Dispatch no.	Date
2019	MIN/2019/ BDR/038	01.06.2019
2013	MIN/2019- BDR/90	04.12.2019
2020	MIN/2020- BDR/0140	01.06.2020
2020	MIN/2020- BDR/0169	02.12.2020
2021	MIN/2021- BDR/087	01.06.2021
	MIN/2021- BDR/058	01.12.2021
2022	MIN/2022-BDR/31	01.06.2022
	MIN/2022-BDR/50	01.12.2022
2023	MIN/BDR/2023/22	01.06.2023
	MIN/BDR/2023/37	01.12.2023
2024	MIN/BDR/2024/13	01.06.2024
	MIN/BDR/2024/26	01.12.2024

53

The environmental statement for each financial Year ending 31st march in form-V as is mandated to be submitted by the project proponent to the Concerned state pollution control board as Prescribed under the environment (protection) Rules, 1986, as amended subsequently, shall also be put on the website of the company along with the status of compliances of EC condition and shall also be sent to the regional office of MoEF.

The environmental statement for financial Year has been submitted to MPPCB Vid letter no. PJL/ENV/F15/2024/862 dated 27/09/2024.





Sample Number : VTL/AA/21

Report No.

: VTL/A/2501250021/A

Name & Address of the Party

: M/s PRISM JOHNSON LIMITED

Format No · 7.8 F-02

Village- Mankahari, Tehsil- Rampur Baghelan, Dist. - Party Reference No Satna (M.P.)

: NIL : 30/01/2025

Report Date Period of Analysis

: 25/01/2025-30/01/2025

Receipt Date

: 25/01/2025

Sample Description

: AMBIENT AIR QUALITY MONITORING

General Information:-

Sampling Location

: Village-Kulhari (Badarkha Mine)

Sample Collected By

VTL Team

Instrument Code

VTL/RDS/FPS/07

Coordinates

: 81.034753 & 24.567341

Meteorological condition during monitoring Date of Monitoring

: Clear Sky

Time of Monitoring

20/01/2025 To 21/01/2025

11:50 to 11:50 Hrs.

Ambient Temperature (°C)

: Min.10°C Max 29°C

Surrounding Activity

: Human, Vehicular & Plant Activities

Method of Sampling Sampling Duration

: IS:5182 24 Hrs.

Parameter Required

: As per work order

S.No.	Parameters	Test Method	Results	Units	NAAQS 2009 (Limits)
1	Particulate Matter (as PM10)	IS:5182 (Part- 23)-2006 RA 2022	68.30	µg/m³	100
2	Particulate Matter (as PM2.5)	IS 5182(Part- 24): 2019	29.68	µg/m³	60
3	Nitrogen Dioxide (as NO2)	IS:5182 (P- 6)-2006, RA.2022	15.73	μg/m³	80
4	Sulphur Dioxide (as SO2)	IS 5182 (Part 2): Sec 1 : 2023	9.09	µg/m³	80
5	Carbon Monoxide (as CO)	IS:5182 (P- 10)-1999, RA. 2019 (NDIR)	0.64	mg/m³	4

*BLQ-Below Limit Of Quantification, **LOQ-Limit Of Quantification

End of Report







RK Yadav Lab Incharge Authorized Signatory



Page No. 1/1

Approved & Certified EPA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified

SC-40, 3rd Floor, Narayan Vihar S, Ajmer Road, Jaipur Raj. 302020

9929108691, 9810205356, 8005707098, 9549956601

www.vibranttechnolab.com





Sample Number: VTL/AA/22

: M/s PRISM JOHNSON LIMITED

Report No.

: VTL/A/2501250022/A

Name & Address of the Party

Format No 7.8 F-02

Village- Mankahari, Tehsil- Rampur Baghelan, Dist. - Party Reference No : NIL

Satna (M.P.)

Report Date

: 30/01/2025

Period of Analysis

: 25/01/2025-30/01/2025

Receipt Date

: 25/01/2025

Sample Description

: AMBIENT AIR QUALITY MONITORING

General Information:-

Sampling Location

: Village-Chulhi (Badarkha Mine)

Sample Collected By

VTL Team

Instrument Code

VTL/RDS/FPS/01

Coordinates

: 81.002619 & 24.594461

Meteorological condition during monitoring

: Clear Sky

Date of Monitoring

: 21/01/2025 To 22/01/2025

Time of Monitoring

: 08:50 to 08:50 Hrs.

Ambient Temperature (°C)

: Min.10°C Max 29°C

Surrounding Activity

: Human, Vehicular & Plant Activities

Method of Sampling Sampling Duration

: IS:5182 : 24 Hrs.

Parameter Required

: As per work order

S.No.	Parameters	Test Method	Results	Units	NAAQS 2009 (Limits)
1	Particulate Matter (as PM10)	IS:5182 (Part- 23)-2006 RA 2022	67.59	µg/m³	100
2	Particulate Matter (as PM2.5)	IS 5182(Part- 24): 2019	31.93	μg/m³	. 60
3	Nitrogen Dioxide (as NO2)	IS:5182 (P- 6)-2006, RA.2022	20.13	µg/m³	80
4	Sulphur Dioxide (as SO2)	IS 5182 (Part 2): Sec 1 : 2023	12.47	µg/m³	80
5	Carbon Monoxide (as CO)	IS:5182 (P- 10)-1999, RA. 2019 (NDIR)	0.71	mg/m³	4

*BLQ-Below Limit Of Quantification, **LOQ-Limit Of Quantification

End of Report







RK Yadav Lab Incharge **Authorized Signatory**



Page No. 1/1

Approved & Certified EPA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified

SC-40, 3rd Floor, Narayan Vihar S, Ajmer Road, Jaipur Raj. 302020







Sample Number: VTL/AA/23

Report No.

: VTL/A/2501250023/A

Name & Address of the Party

: M/s PRISM JOHNSON LIMITED

: 7.8 F-02 Format No

Village- Mankahari, Tehsil- Rampur Baghelan, Dist. - Party Reference No : NIL

Satna (M.P.)

Report Date : 30/01/2025

Period of Analysis

: 25/01/2025-30/01/2025

Receipt Date

: 25/01/2025

Sample Description

: AMBIENT AIR QUALITY MONITORING

General Information:-

Sampling Location

: Village-Hinauta (Badarkha Mine)

Sample Collected By

VTL Team

Instrument Code

VTL/RDS/FPS/02

Coordinates

: 80.985206 & 24.569934

Meteorological condition during monitoring

: Clear Sky

Date of Monitoring

: 21/01/2025 To 22/01/2025

Time of Monitoring

: 09:25 to 09:25 Hrs.

Ambient Temperature (°C)

: Min.10°C Max 29°C

Surrounding Activity

: Human, Vehicular & Plant Activities

Method of Sampling Sampling Duration

: IS:5182 : 24 Hrs.

Parameter Required

: As per work order

S.No.	Parameters	Test Method	Results	Units	NAAQS 2009 (Limits)
1	Particulate Matter (as PM10)	IS:5182 (Part- 23)-2006 RA 2022	74.63	µg/m³	100
2	Particulate Matter (as PM2.5)	IS 5182(Part- 24): 2019	31.94	μg/m³	60
3	Nitrogen Dioxide (as NO2)	IS:5182 (P- 6)-2006, RA.2022	17.39	µg/m³	80
4	Sulphur Dioxide (as SO2)	IS 5182 (Part 2): Sec 1 : 2023	13.20	µg/m³	80
5	Carbon Mohoxide (as CO)	IS:5182 (P- 10)-1999, RA. 2019 (NDIR)	0.70	mg/m³	4

*BLQ-Below Limit Of Quantification, **LOQ-Limit Of Quantification

End of Report







RK Yadav Lab Incharge Authorized Signater



Page No. 1/1

Approved & Certified EPA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified





Sample Number : VTL/AA/24

Name & Address of the Party : M/s PRISM JOHNSON LIMITED

Report No. : VTL/A/2501250024/A

Format No - 7.8 F-02

Village- Mankahari, Tehsil- Rampur Baghelan, Dist. -Satna (M.P.)

Party Reference No : NIL

Report Date

: 25/01/2025-30/01/2025

Period of Analysis Receipt Date

: 25/01/2025

: 30/01/2025

Sample Description

: AMBIENT AIR QUALITY MONITORING

General Information:-

Sampling Location

Village-Badarkha (Badarkha Mine)

Sample Collected By

VTL Team

Instrument Code

VTL/RDS/FPS/03

Coordinates

80.982443 & 24.584626

Meteorological condition during monitoring

Date of Monitoring

: Clear Sky

Time of Monitoring

: 21/01/2025 To 22/01/2025

: 10:00 to 10:00 Hrs.

Ambient Temperature (°C)

: Min.10°C Max 29°C

Surrounding Activity

: Human, Vehicular & Plant Activities

Method of Sampling Sampling Duration

: IS:5182 24 Hrs.

Parameter Required

: As per work order

S.No.	Parameters	Test Method	Results	Units	NAAQS 2009 (Limits)
1	Particulate Matter (as PM10)	IS:5182 (Part- 23)-2006 RA 2022	75.22	µg/m³	100
2	Particulate Matter (as PM2.5)	IS 5182(Part- 24): 2019	40.80	µg/m³	60
3	Nitrogen Dioxide (as NO2)	IS:5182 (P- 6)-2006, RA.2022	22.91	µg/m³	80
4	Sulphur Dioxide (as SO2)	IS 5182 (Part 2): Sec 1 : 2023	14.20	µg/m³	80
5	Carbon Monoxide (as CO)	IS:5182 (P- 10)-1999, RA. 2019 (NDIR)	0.73	mg/m³	4

*BLQ-Below Limit Of Quantification, **LOQ-Limit Of Quantification

***End of Report**









RK Yadav Lab Incharge Authorized Signatory



Page No. 1/1

Approved & Certified EPA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified



9 SC-40, 3rd Floor, Narayan Vihar S, Ajmer Road, Jaipur Raj. 302020







Sample Number : VTL/W/08

Name & Address of the Party : M/s PRISM JOHNSON LIMITED

: Badarkha Village -Borewell

: Suitable Preservation

Village- Mankahari, Tehsil- Rampur Baghelan, Dist. -

Satna (M.P.)

: Water Sample

ULR No.

: TC1122725000000266F

Report No.

: VTL/W/2501250008/A

Format No

: 7.8 F-01

: 30/01/2025

Party Reference No

: NIL

Report Date Period of Analysis

: 25/01/2025-30/01/2025

Receipt Date

: 25/01/2025

Sampling Date

: 21/01/2025

Sampling Type Sample Quantity : Grab

: 2 Ltr.

Method of sampling

Preservation

Sample Description

Sampling Location

Sample Collected By

: IS:3025

: VTL Team

Coordinates :--

S.No.	Test Parameters	Test Method	Results	Units	IS:10500-2012,RA 2023	
					Acceptable Limit	Permissible Limit
1	pH (at 25°C)	IS: 3025 (P-11): 2022	7.30	-	6.5 to 8.5	No Relaxation
2	Colour	IS: 3025:(P-4): 2021	*BLQ(**LOQ-1.0)	Hazen	5	15
3	Turbidity	IS: 3025: (P-10): 2023	*BLQ(**LOQ-1.0)	NTU	1	5
4	Odour	IS: 3025 (P-5): 2018	Agreeable		Agreeable	Agreeable
5	Taste	IS :3025 (P-8): 2023	Agreeable	-	Agreeable	Agreeable
6	Total Hardness (as CaCO3)	IS: 3025 (P-21): 2009, RA 2019	219.0	mg/L	200	600
7	Calcium (as Ca)	IS: 3025 (P- 40): 2024	58.9	mg/L	75	. 200
8	Total Alkalinity (as CaCO3)	IS: 3025 (P-23): 2023	253.0	mg/L	200	600
9	Chloride (as CI)	IS: 3025 (P-32): 1988, RA 2019	108.0	mg/L	250	1000
10	Magnesium (as Mg)	IS: 3025 (P-46): 2023	17.51	mg/L	30	100
11	Total Dissolved Solids	IS :3025 (P-16): 2023	611	mg/L	500	2000
12	Sulphate (as SO4)	IS: 3025 (P-24): Sec : 1 : 2022	39.20	mg/L	200	400
13	Fluoride (as F)	APHA 24th Edition, 4500F-D: 2023	0.40	mg/L	1.0	1.5
14	Nitrate (as NO3)	IS 3025 (P-34) : Sec 1 : 2023 (Clause 6.4)	he u19.30 mag	mg/L	45.0	No Relaxation
15	Iron (as Fe)	APHA 24th Edition 3111 B, 2023	0.32	mg/L	1.0	No Relaxation
16	Aluminium (as Al)	IS 3025 (P-55): 2003, RA 2019	*BLQ(**LOQ-0.03)	mg/L	0.03	0.2
17	Boron (as B)	APHA 24th Edition 4500B-C : 2023	*BLQ(**LOQ-0.2)	mg/L	0.5	2.4
18	Total Chromium (as Cr)	APHA 24th Edition 3111 B, 2023	*BLQ(**LOQ-0.02)	mg/L	0.05	No-Relaxation








RK Yadav Lab Incharge Authorized Signatory



Page No. 1/2



Approved & Certified EPA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified





Sample Number :

ULR No.

: TC1122725000000266F

Report No.

: VTL/W/2501250008/A

	77277700		Report	NO.	: VIL/W/25012	50006/A
S.No.	Test Parameters	est Parameters Test Method	Results	Units	IS:10500-2012,RA 2023	
					Acceptable Limit	Permissible Limit
19	Zinc (as Zn)	APHA 24th Edition 3111 B, 2023	0.44	mg/L	5.0	15.0
20	Copper (as Cu)	APHA 24th Edition 3111 B, 2023	*BLQ(**LOQ-0.02)	mg/L	0.05	1.5
21	Manganese (as Mn)	APHA 24th Edition 3111 B, 2023	*BLQ(**LOQ-0.05)	mg/L	0.1	0.3
22	Cadmium (as Cd)	APHA 24th Edition 3111 B, 2023	*BLQ(**LOQ-0.002)	mg/L	0.003	No Relaxation
23	Lead (as Pb)	APHA 24th Edition 3111 B, 2023	*BLQ(**LOQ-0.005)	mg/L	0.01	No Relaxation
24	Arsenic (as As)	APHA 24th Edition 3114 C, 2023	*BLQ(**LOQ-0.005)	mg/L	0.01	0.05
25	Mercury (as Hg)	APHA 24th Edition 3112B: 2023	*BLQ(**LOQ-0.001)	mg/L	0.001	No Relaxation
	Total Coliform	IS: 15185: 2016 RA: 2021	Absent	per 100 ml	Shall not be detectable in any 100 ml sample	-
	E.Coli	IS: 15185: 2016 RA: 2021	Absent	per 100 ml	Shall not be detectable in any 100 ml sample	
28	Sulphide (as H2S)	IS 3025 (P-29) : 2022 (Clause 7.0)	*BLQ(**LOQ-0.04)	mg/L	0.05	No Relaxation
29	Nickel as Ni	APHA 24th Edition 3111 B, 2023	*BLQ(**LOQ-0.01)	mg/L	0.02	No relaxation
BO	Free Residual Chlorine	IS 3025 (P- 26): 2021 (Clause 7.0)	*BLQ(**LOQ-0.2)	mg/L	0.2	1.0

^{*}BLQ-Below Limit Of Quantification, **LOQ- Limit of Quantification

End of Report







RK Yadav Lab Incharge Authorized Signatory



Approved & Certified EPA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified

Page No. 2/2

SC-40, 3rd Floor, Narayan Vihar S, Ajmer Road, Jaipur Raj. 302020

9929108691, 9810205356, 8005707098, 9549956601



M bd@vibranttechnolab.com

www.vibranttechnolab.com



Name & Address of the Party:

Sample Collected By

Sample Description:

VTL/WL/01-14

M/s PRISM JOHNSON LIMITED Village- Mankahari, Tehsil- Rampur

Baghelan, Dist.- Satna (M.P.)

VTL Team

Ground Water Level Monitoring

Report No.: Format No.:

VTL/WL/2501250001-14/B

7.8 F-01

Party Reference No.:

NIL

Report Date: **Receipt Date:** 30/01/2025

25/01/2025

Date of Monitoring

18-22/01/2025

S.No.	Location	Depth (In meter)
1.	Near Colony Gate	
2.	Behind B Block colony	8.54
3.	Behind C Block colony	7.43
4.	Near Auto Work Shop	5.6
5.		11.2
6.	In Front of Den	7.61
	Western Block Mines	09.10
7.	Near New Magazine Mines	15.0
8.	Rose Garden Near Road	08.14
9.	Mines near Ramprasan	15.8
10.	Medhi Mines	13.3
11.	Mankahari Mines	12.0
12.	Chulhi Majhiyar Mines	
13.	Bagahai Mines	10.2
14.	Badarkha Mines	8.71
		10.8

RK Yadav Lab Incharge Authorized Signatory

Approved & Certified EPA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified





Experience the unimaginable" Sample Number: VTL/AN/21

Name & Address of the Party : M/s PRISM JOHNSON LIMITED Report No.

: VTL/N/2501250021/A

Village- Mankahari, Tehsil- Rampur Baghelan, Dist. - Party Reference No Satna (M.P.)

Format No

Calibration Status

- 7.8 F-04

Report Date

: NIL

: 30/01/2025

Receipt Date

: 25/01/2025

: Ambient Noise Level Monitoring

Sampling Duration : 24 Hrs.

Sample Collected

: VTL Team

Instrument

- Calibrated

Sample Description Scope of Monitoring

: Regulatory Requirment

Protocol Used

: IS 9989

Instrument Used

: SLM

General Information:-

Sampling Location

Village-Kulhari (Badarkha Mine)

Instrument Code

VTL/SLM/07

Meteorological condition during monitoring

: Clear Sky

Date of Monitoring

: 20/01/2025 To 21/01/2025

Time of Monitoring

06:00 to 06:00 Hrs.

Ambient Temperature (°C)

: Min.10°C Max 29°C

Surrounding Activity

: Human, Vehicular & Other Activities

Parameter Required

As per Work Order

Coordinates

S.No.	Test Parameters	Protocol	Test Result dB(A)		
			Day Time	Night Time	
1	Noise Level (Leq)	IS 9989 - 1981 RA:2020	49.9	38.5	

Ambient Noise Quality Standards as per Noise Pollution (Regulation and Control) Rules

Area Code	Category of Area/Zone .	Limits	in dB(A) Leq*
		Day Time	Night Time
A	Industrial area	75	70
В	Commercial area	65	55 '
С	Residential area	55	45
D	Silence Zone	50	40

1. Day Time is from 6.00 AM to 10.00 PM.

Note: Mixed categories of areas be declared as one of the four above mentioned categories by the competent Authority and the corresponding standards shall apply

End of Report







RK Yadav Lab Incharge Authorized Signatory



Approved & Certified EPA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified

Page No. 1/1

Vibrant Techno Lab Pvt. Ltd.

9 SC-40, 3rd Floor, Narayan Vihar S, Ajmer Road, Jaipur Raj. 302020

9929108691, 9810205356, 8005707098, 9549956601

2 0141-2954638

M bd@vibranttechnolab.com

www.vibranttechnolab.com

Night Time is reckoned between 10.00 PM to 6.00 AM.
 Silence Zone is defined as an area up to 100 m around premises of Hospitals, Educational and Courts. Use of vehicle horn, Loudspeaker and bursting of crackers is banned in these zones.





Sample Number : VTL/AN/22

Name & Address of the Party : M/s PRISM JOHNSON LIMITED

Report No.

: VTL/N/2501250022/A

Format No

: 7.8 F-04

Village- Mankahari, Tehsil- Rampur Baghelan, Dist. -Satna (M.P.)

Party Reference No Receipt Date

· NII

Report Date

: 30/01/2025 : 25/01/2025

Sample Description

: Ambient Noise Level Monitoring

Sampling Duration

: 24 Hrs.

Scope of Monitoring

: Regulatory Requirment

Sample Collected

: VTL Team

Protocol Used

: IS 9989

Instrument Used

: SLM

Instrument Calibration Status · Calibrated

General Information:-

Sampling Location

Village-Chulhi (Badarkha Mine)

Instrument Code

VTL/SLM/01

Meteorological condition during monitoring

: Clear Sky

Date of Monitoring

21/01/2025 To 22/01/2025

Time of Monitoring

: 06:00 to 06:00 Hrs.

Ambient Temperature (°C)

: Min.10°C Max 29°C

Surrounding Activity

: Human, Vehicular & Other Activities

Parameter Required

: As per Work Order

Coordinates

S.No.	Test Parameters	Protocol	Test Re	sult dB(A)
			Day Time	Night Time
1	Noise Level (Leq)	IS 9989 - 1981 RA:2020	48.6	37.1

Ambient Noise Quality Standards as per Noise Pollution (Regulation and Control) Rules, 2000

Area Code	Category of Area/Zone	Limits	Limits in dB(A) Leq*		
		Day Time	Night Time		
A	Industrial area	75	70		
В	Commercial area	65	55		
С	Residential area	55	45		
D	Silence Zone	50	40		

^{1.} Day Time is from 6.00 AM to 10.00 PM.

End of Report







RK Yadav Lab Incharge Authorized Signator



Approved & Certified EPA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified

Page No. 1/1



SC-40, 3rd Floor, Narayan Vihar S, Ajmer Road, Jaipur Raj. 302020



^{2.} Night Time is reckoned between 10.00 PM to 6.00 AM.

^{3.} Silence Zone is defined as an area up to 100 m around premises of Hospitals, Educational and Courts. Use of vehicle horn, Loudspeaker and bursting of crackers is banned in

Note: Mixed categories of areas be declared as one of the four above mentioned categories by the competent Authority and the corresponding standards shall apply





Sample Number :

Report No.

: VTL/N/2501250023/A

Name & Address of the Party

: M/s PRISM JOHNSON LIMITED

Format No

7.8 F-04

Village- Mankahari, Tehsil- Rampur Baghelan, Dist. -Satna (M.P.)

Party Reference No

· NII

Report Date Receipt Date : 30/01/2025

: 25/01/2025

Sample Description

: Ambient Noise Level Monitoring

Sampling Duration

: 24 Hrs.

Scope of Monitoring

: Regulatory Requirment

Sample Collected

: VTL Team

Protocol Used

: IS 9989

Instrument

Calibrated

Instrument Used

: SLM

Calibration Status

General Information:-

Sampling Location

Village-Hinauta (Badarkha Mine)

Instrument Code

VTL/SLM/02

Meteorological condition during monitoring

: Clear Sky

Date of Monitoring

21/01/2025 To 22/01/2025

: 06:00 to 06:00 Hrs.

Time of Monitoring

Ambient Temperature (°C)

: Min.10°C Max 29°C

Surrounding Activity

: Human, Vehicular & Other Activities

Parameter Required

: As per Work Order

Coordinates

S.No.	Test Parameters	Protocol	Test Result dB(A)	
4			Day Time	Night Time
1	Noise Level (Leq)	IS 9989 - 1981 RA:2020	53.3	42.7

Area Code	Category of Area/Zone	Limits i	Limits in dB(A) Leq*	
		Day Time	Night Time	
A	Industrial area	75	70	
В	Commercial area	65	55	
С	Residential area	55	45	
D	Silence Zone	50	40	

^{1.} Day Time is from 6.00 AM to 10.00 PM.

Note: Mixed categories of areas be declared as one of the four above mentioned categories by the competent Authority and the corresponding standards shall apply

End of Report







RK Yadav Lab Incharge Authorized Signatory



Approved & Certified EPA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified

Page No. 1/1



SC-40, 3rd Floor, Narayan Vihar S, Ajmer Road, Jaipur Raj. 302020



^{2.} Night Time is reckoned between 10.00 PM to 6.00 AM.

^{3.} Silence Zone is defined as an area up to 100 m around premises of Hospitals, Educational and Courts. Use of vehicle horn, Loudspeaker and bursting of crackers is banned in





Sample Number : VTL/AN/24

: M/s PRISM JOHNSON LIMITED

Report No.

: VTL/N/2501250024/A

Name & Address of the Party

Village- Mankahari, Tehsil- Rampur Baghelan, Dist. - Party Reference No

Format No

7.8 F-04

Satna (M.P.)

Report Date

: NIL : 30/01/2025

Receipt Date

: 25/01/2025

Sample Description Scope of Monitoring : Ambient Noise Level Monitoring

Sampling Duration

: 24 Hrs.

Protocol Used

: Regulatory Requirment

Sample Collected

: VTL Team

Instrument Used

: IS 9989 : SLM

Instrument Calibration Status

Calibrated

General Information:-

Sampling Location

Village-Badarkha (Badarkha Mine)

Instrument Code

VTL/SLM/03

Meteorological condition during monitoring

: Clear Sky

Date of Monitoring

: 21/01/2025 To 22/01/2025

Time of Monitoring

: 06:00 to 06:00 Hrs.

Ambient Temperature (°C)

: Min.10°C Max 29°C

Surrounding Activity

: Human, Vehicular & Other Activities

Parameter Required

As per Work Order

Coordinates

S.No.	Test Parameters	Protocol	Test Result dB(A)	
			Day Time	Night Time
1	Noise Level (Leq)	IS 9989 - 1981 RA:2020	47.1	38.9

Area Code	Category of Area/Zone	Limits	Limits in dB(A) Leq*	
		Day Time	Night Time	
A	Industrial area	75	70	
В	Commercial area	65	55	
С	Residential area	55	45	
D	Silence Zone	50	40 '	

^{1.} Day Time is from 6.00 AM to 10.00 PM.

End of Report







RK Yadav Lab Incharge Authorized Signatory



Approved & Certified EPA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified

Page No. 1/1



SC-40, 3rd Floor, Narayan Vihar S, Ajmer Road, Jaipur Raj. 302020







^{2.} Night Time is reckoned between 10.00 PM to 6.00 AM.

^{3.} Silence Zone is defined as an area up to 100 m around premises of Hospitals, Educational and Courts. Use of vehicle horn, Loudspeaker and bursting of crackers is banned in

Note: Mixed categories of areas be declared as one of the four above mentioned categories by the competent Authority and the corresponding standards shall apply

Report on Scientific Study on Controlled Blasting at Badarkha Limestone Mines

of

M/s Prism Johnson Ltd, Dt. Satna (M.P.)

Project Number: 31/2018-19

Project Leader

Prof G.K.Pradhan

Project Collaborators

Ajeet Mehra, M.Tech(Mining), Asst. Professor

Department of Mining Engineering

December 2019



Acknowledgement

Department of Mining Engineering, Faculty of Engineering & Technology, AKS University, Satna (MP) acknowledges with thanks the support and cooperation extended by:

- 1. Shri Manoj Singh, head-Mines, Prism Johnson Ltd
- 2. Shri C.S.Pandit, Joint General Manager, Prism Johnson Ltd
- 3. Sri Deo Prakash, Mines Manager-cum-Blasting Manager
- 4. Sri Kamlesh Soni, Asst. Manager

We thank the Management of AKS University, Satna for giving us permission to undertake the Study and the following team members for their active support and co-operation:

- 1. Dr B.K.Mishra, Head of the Department, Mining Engineering
- 2. Sri Ajeet Mehra, Asst. Professor (Mining)
- 3. Sri Manish Agarwal, Asst. Prof(Physics), Coordinator, Dean Office

We are pleased to present our Report on this scientific study based on our field visits and analyses of data collected from the mines vis-à-vis various Regulatory requirements.

Prof G.K.Pradhan

Recipient of National Geosciences Award Professor of Mining Engineering & Dean Faculty of Mining Engineering

Email: gkpradhan58@gmail.com

While granting Consent to Operate under section 25 of the Water (Prevention & Control of Pollution) Act, 1974 under section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization under Hazardous and other Waste (Management & Tran boundary Movement) Rules, 201, vide PCB ID: 14462 dated 30.6.2018, it was stated at *Sl. No. 14. Controlled blasting should be practiced with the use of delay detonators and only during daytime. The mitigative measures for control of ground vibrations and to arrest the fly rocks and boulders should be implemented. Blasting shall be done during day time only.* Copy of the Consent to operate is placed at Annexure I.

The Department of Mining Engineering, AKS University, Satna was entrusted to design, evaluate/supervise/monitor the 'controlled blasting' as per the provisions of MMR 1961 and the Permission granted by Director of Mines Safety, Jabalpur (DGMS Office).

Vide letter no. J.R/Metal/Permission-34/2016/77 dated 6.1.17, DMS Jabalpur Region had granted exemption from the provisions of Metalliferous Mines Regulations (MMR) 1961, 106(2)(b) of MMR, 1961, to work by system of deep hole blasting and deployment of Heavy Earth Moving Machineries. Sl. No. 7.0, 8.0, sl. No. 23(4), (5), (7), indicated various precautions to be taken to ensure safety while blasting. Copy of the Permission is placed at Annexure II. The above Permission was later supplemented with the Deep hole Blasting Permission for use of Bulk SME Explosives.

The scientific study undertaken by AKS University covered –

- a) Blasting techniques for Over Burden and Limestone benches.
- b) Site visits to monitor adoption of safe procedures during handling, transport, and use of explosives and accessories as per S-O-P
- c) Study of Explosive use and optimisation
- d) Study of Initiation system as a part of Controlled blasting
- e) Management of blasting operation and schedule vis-à-vis blasting during daytime.
- f) Methods for monitoring, analyses of ground vibrations and associated problems as part of mitigative measure.
- g) Study of fly rocks and boulders during blasting and strict implementation of methods to reduce their generation etc.
- h) Training the workmen, supervisors and officials attached with blasting.

Blasting Manpower

Entire blasting operation is undertaken under the charge of the Mines Manager, holdiong First Class Mine Manager's Certificate of Competency (UR). He is being assisted by statutory persons as per provisions of MMR 1961, including Blasting Engineer, Blaster, Helpers, Mining Mate and others.

Selection, Procurement, Storage, Transport and Handling of Explosives

During the study period the various activities involved in explosives and accessories selection, procurement, storage, transport and use have been studied. The Mine holds a valid Explosive Magazine Licence and Explosive Transport by approved type of Explosive vans, as per various provisions of Indian Explosives Rules, 2008.

The mine uses only cartridge type explosives and have a system of explosive selection based on

- Density,
- Velocity of Detonation (VOD) etc.

The pattern of procurement is high energy primer 25 % and 75% column charge. The handling, charging and conducting of the blasting operations is done by trained manpower of the mine. Table 1, presents the quantities of different types of explosives used in study in the mine.

Table 1: Presents the quantities of different types of explosives used in study in the mine

Year	Large dia Cartridge Large dia Cart		Total
	explosives (kg)	explosives (kg)	Explosives
	(Column charge)	(Booster charge)	Qty(in kgs)
2018	1450	383.32	1833.32
2019	3987.1	1350.00	5337.1

Initiation system

Initiation of the primed cartridge of the explosive in 100 to 110 mm dia blast hole drills is an essential feature to trigger any blast. In these blast holes blasting of deep holes column charge is being primed by booster type of explosives. Shock tubes having 7 to 8m length is used down-the-hole, along with the surface trunk line shock tubes. Down-the-delay detonator of 25, 450MS had provided bottom initiation and Trunk line detonators of 17, 25 and 41 MS are used thereby providing hole to hole initiation.

Use of Shock Tubes(Nonel)

This as entirely non-electric and ultra safe. Shock tubes(Nonel) are safest and offer excellent results in blasting. These have revolutionised initiation by offering true in-hole delay to the booster ensuring better movement of the shock waves and the blasted material. The very low content of explosive material in the plastic tube offers insignificant or no sound during blasting. True bottom priming has enhanced explosive use and also helped in planning large size blasts safely. Trunk line delay detonators in the shock tubes additionally eliminate sound and also ensure perfect blast timings in MS range. Thus there has been a fall in sound level (expressed in dB) as recorded in the blast vibration recorder, control on fly rocks, elimination of misfires, and maintaining MAXIMUM CHARGE PER DELAY which is the single most contributing factor for BLAST VIBRATION level. Table 2, shows the DGMS standard on blast vibration and this is being strictly followed in almost all blasts.

Pre and Post Blast Management

In compliance of provisions under MMR 1961 and Indian Explosives Rules 20008, and various norms set in S-O-P and DMS JR Permissions/DGMS Circulars each and every blast is undertaken. The blast details are recorded and maintained in the mine.

Mining Operations

Figure 1, presents the approved working plan of the mine. The mine had a single overburden bench comprising of top soil and sub soil which is handled purely by dozer and loading machines. The limestone bench below having a thickness of 5 to 15m, is mined in two to three benches. Each bench has been planned with 5 to m6 m height only. Hydraulic Excavators dig the un-blasted as well as blasted material and load into tippers. Figure 1, shows the site plan showing limestone bench where blasting is conducted.

Controlled blasting is defined as a blast in which –

- (1) All the blast design parameters at the blasting site.
- (2) Blast which was approved type of explosives.
- (3) Only Delay detonators including Shock tubes(Nonel) or Electronic Delay Detonators to be used (to control ground vibrations and to arrest flyrocks and boulder generations).
- (4) Monitoring of blasts vis-à-vis blast induced ground vibration level & frequency (Hz). Examining the vibration level (mm/s) & frequency with DGMS standards.
- (5) Following all terms and conditions as stated in the Permission granted by Director of Mines Safety, Jabalpur vide J.R/Metal/Permission -34/2016 dated 06-01-2017 (Copy enclosed). Also following norms of other statutory bodies.
- (6) Flyrock management ,generation and control by proper stemming by assuming proper free face ensuring use of quality and explosives & accessories. There by eliminating MISFIRES.
- (7) Following approval S-O-P for blasting.
- (8) Minimum generation of boulders thereby eliminating secondary blasting. However secondary blasting need to be replaced by use of Hydraulic Rock breakers only be replaced by use of Hydraulic Rock Breakers only.
- (9) Complained free or less complaints from nearby habitants.
- (10) Only during the day time and the blasting time should be prominently displayed in the area.
- (11) Every mine should draw plans to have mitigative measures as per recommendations of the scientific study and provisions of MMR 1961 or DGMS Guidelines.

Blast Measurement

Instantel Inc. Canada make Blast Vibration instrument is being used by the mine management to record blast vibration level, sound level and maintain the soft copy of each and every recorded blasts for analysis and review. From AKS University also Instantel make Blastmate Instrument is used. These instruments are regularly calibrated by the authorised representative/agency.

Table 2 : DGMS Standards (1997)

Type of structure	Dominant excitation frequency, Hz				
	< 8 Hz	8 - 25 Hz	> 25 Hz		
(A) Buildings/structures not belonging to the owner					
i) Domestic houses/structures (Kuchha brick and cement)	5	10	15		
ii) Industrial Buildings RCC and framed structures)	10	20	25		
iii)Objects of historical importance and sensitive	2	5	10		
structures					
(B) Buildings belonging to owner with limited span of life					
i) Domestic houses/structures (Kuchha brick and cement)	10	15	25		
ii) Industrial buildings (RCC & framed structures)	15	25	50		




Figure 1 : Showing the Working Plan of the Mine

Figure 2, shows the print out of the Blast Vibration and Sound level as recorded at the blast site. The other such reports are placed at Annexure 1. Table 3: presents the blast design information of the blasts which were studied and monitored by AKS University.

Table 2: Blast Design Information's Using Cartridge Explosives

Hole diameter = 100 to 110 mm

Max. Burden = 4 M

Max. Spacing = 3 M

Average Hole depth = 5 to 6.0 M.

No. of holes = as per blasting block size and maintaining face length and width in 3:1 ratio

Drilling pattern = staggered

Average Stemming length =2 to 3 M

Firing pattern = linear

No. of rows depend on the block size and face conditions

Explosives

Prime charge and column charge at an average ratio of: 1: 2.5

Delay Type

Surface delay = 17 MS (hole to hole in a row) & 25 MS and/or 42 MS (row to row)

Down the hole delay = 250 ms

Trial blast data was analyzed for arriving at permissible levels of ground vibration and same is presented in Table 3. Table 4, presents the analysis of blast vibration data. Predictor Equation has been drawn based on the field data as recorded.

Table 3: SUMMARY OF BLASTS - GROUND VIBRATION RCORDED AT BADARKHA MINE

Blast	Date	Radial	Max	Total	PPV	Frequency	Burden	No.	Avg.
No.		distance	charge	weight	(mm/sec.	Hz	X	of	Hole
		(m)	per	(TQ))		Spacing	holes	Depth
			delay	(kg)					(m)
			(Q)(kg)						
1	06-02-2018	250	16.7	433.32			4x3	30	5
2	08-05-2018	250	13.9	325			4x3	25	5
3	04-12-2018	160	16.70	325	0.126	4.2	4x3	20	5
4	31-12-2018	200	27.78	750	2.52	23	4x3	27	6
5	01-03-2019	180	19.44	725	1.54	15	4x3	37	5
6	05-03-2019	160	22.22	1325	1.927	15	4x3	64	5.5
7	11-03-2019	250	30.56	2211.11	2.136	12	4x3	78	6
8	19-03-2019	200	27.78	1075	5.56	16	4x3	41	6

Figure 2 : Shows Blast Vibration recording Event report(Other reports at Annexure 1)

Event Report Instantel Tran at 13:41:35 December 31, 2018 Serial Number UM8131 V 10-76 Micromate ISEE Trigger Source Geo: 0.900 mm/s, Mic: 2.000 pa.(L) Battery Level 3.8 Volts Unit Calibration February 26, 2018 by UES New Delhi Geo: 254 0 mm/s Range Record Time 5.0 sec at 1024 sps File Name UM8131_20181231134135.IDFW Operator/Setup: Operator/SSB.mmb Post Event Notes Bandarkha/1st Bench (L/S), No of holes 27 nos, Depth - 8.0 Mtrs. Notes Charge/delay - 27.77 Kg/delay, Obsevation Distance - 160 mts Client: User Name: PRISM JOHNSON LIMITED DGMS India (A) Extended Notes BANDARKHA LIMESTONE MINE Microphone Linear Weighting 15.69 pa.(L) at 0.597 sec ZC Freq 23 Hz Channel Test Passed (Freq = 19.7 Hz Amp = 1307 mv) 50 Velocity (mm/s) Tran Vert Long 2.262 1.745 2.396 1.624 mm/s 20 PPV (Ponderated) 2.012 1.506 mm/s PPV 58.09 58.59 55.21 dB ZC Freq 37 Hz Time (Rel. to Trig) 0.359 0.250 0.317 sec Peak Acceleration 0.056 0.043 0.054 8 Peak Displacement 0.043 0.012 0.011 mm Sensor Check Frequency 7.3 7.3 Hz Overswing Ratio 3.4 3.6 3.7 Peak Vector Sum 2.520 mm/s at 0.358 sec Frequency (Hz) Tran: + Vert: x Long: 0 a)Industrial Buildings b)Domestic houses/structures c)Historic objects, sensitive structu MicL 0.0 0.0 Long Vert 0.0

Figure - 4: Below explains the method of blasting using trunk line shock tubes of varying delays and.

1.0

Format @ 1995-2014 Xmark Corporation

Time scale has been modified and may not represent the actual length of the event record Time Scale: 0.20 seo'div_ Amplitude Scale: Geo: 2.000 mm/s/div Mic: 5.000 ps.(L)/div 0.0


2.0

Sensor Check

Tran


0.0

Printed: February 3, 2022 (V 10.72 - 10.72)



1. Vibration predictor equation : For total charge per round (TQ)

$$PPV = 31.40 * (\frac{D}{\sqrt{TQ}})^{-0.173}$$



2. Ground vibration predictor equation : for max charge per delay(Q)

$$PPV = 0.056 * (\frac{D}{\sqrt{Q}})^{0.032}$$




Table 4: Analysis of blast monitoring data

Parameter	Range	Class	No. of events	Remark
		interval		
Max.Charge	14.75 to 27.77	0-20	5	
Per Delay (kg)		>20	3	Within stipulated
PPV (mm/sec.)	0.126 to 5.56	<2	5	limits
		2-6	3	
Distance (m)	160 to 250	160 to 250	8	
Frequency	<8I	Hz	0	More than 71% event
(Hz)	8-25Hz	Hz	8	recorded more than 8
	>25	Hz	0	Hz. This has bearing on fixing allowable PPV.

RECOMMENDATIONS & SUGGESTIONS

For undertaking blasts with Cartridge Explosives on regular basis the conclusion/completion of blasts conducted in our presence, as per terms and conditions of the Permission Director of Mines Safety, Jabalpur vide by No.J.Region/Metal/Permission-34/2016/77 dated 6.1.17, regarding Relaxation from the provisions of Regulation 106(2)(b)of the Metalliferous Mines Regulations, 1961, to work the mine by system of deep hole blasting and deployment of Heavy Earth Moving Machineries at Badarkha Limestone Mine of M/s Prism Cement Limited and norms of Consent Order of M.P.Pollution Control Board (sl. No. 14 at page no. page8, 'Controlled blasting should be practiced with the use of delay detonators and only during daytime. The mitigative measures for control of ground vibrations and to arrest the fly rocks and boulders should be implemented. Blasting shall be done during day time only'.).

Some of the salient clasues related to Explosives and Blasting(Shot firing) is stated at Annexure 2 (p.1, 3,4 and 5).

Blast design parameters


1.1 Drilling dia. of 100-110 mm is best suited for 6m high benches. For 100-110 mm dia blast hole the true burden may be 2.5 to 4.0 M and true spacing of 3.0 to 4.5m.

		Pattern (Maximum)			
Depth (m)	Hole dia (mm)	Burden (m)	Spacing (m)		
6	110	4	3		
5	110	4	3		
4	110	4	3		
3	110	4	3		

1.2 No. of Rows – During the trial blast the length of the blast was more than the width of the blast. In most blasts length of the blasting block has been more than 5 to 6 times the width of the blasted block. In these cases number of rows can result PPV within laid down norms and a maximum of 6 rows are recommended. For example – if length of the blasting block is 100M, and width is 30 M with true burden of 3m then no. of rows should not exceed 9 Rows. This is because more number of rows may result in cut off of the tie-ins.

2.0 Initiation arrangements/tie-ins

- 2.1 NONEL which has been used is best suitable to contain blast induced ground vibration and air blast. Besides, it also give very good fragmentation, less back break, and controlled throw on free face.
- 2.1.1 The delay between the hole is 17 MS and between rows may be 42 MS (Refer attached figure).-



- 2.1.2 Misfires can be totally eliminated with the use of NONEL or shock tubes.
- 2.1.3 Using a high delay interval of 250 MS down-the-hole delay with 17/25/42MS surface delay ensures that the detonation of the surface tie line would be several rows or blast holes ahead before the first blasthole gets initiated (after 250MS) and ground movement starts subsequently. This makes the blast free from any misfires due to initiation resulted by cut-off of in hole or downline initiator due to ground movement. Besides, the very geology of the area also indicate near uniformity of geological set up.
- **3.0 SUGGESTIONS WHICH WERE IMPLEMENTED AT SITE** The blast hole initiation pattern should use one delay period of 17 MS between the two holes and 42 MS between the rows.
- 3.1.1 Initiation pattern While drilling holes staggered pattern may be adopted. It has been observed that staggered pattern with equilateral triangular give better fragmentation as compared to square pattern. During trial blasts square pattern was adopted and results were quite satisfactory.
- 3.1.2 Period of blast The total period of blast from the initiation of the first hole to the last hole should preferably be not more than 1000 MS

4.0 Before commencing Drilling

- 4.1 Face preparation before commencement of drilling The bench must be properly dozed to ensure no flying fragments of the previous blast or boulders are present. On the free face side the face need to be dressed properly so that no loose overhangs are present. The blaster must mark the location of holes after measuring the burden and spacing. The driller must report any deviations observed in burden and spacing and also hole collapse during withdrawal of the drill rod.
- 4.2 Free Face The key to success of any safe blast is the free face. It must be noted that the direction of throw must be towards free face. Whenever two free faces are available, the direction of throw can be diagonal for better muckpile and uniform throw.

5.0 Stemming and stemming material

- 5.1 To hold the post detonation fumes inside the blasthole is essential to ensure movement and breakage of the in-situ rock. The blasting crew should have specially trained workmen who can ensure tight stemming. If watery holes are encountered it has to be with lot of care so as to ensure settlement of explosive and stemming material. In all the blasts dry drill cuttings were used and care was taken to see no damages to the shock tube down-line.
- 5.2 It is suggested to measure the stemming column depth so as to ensure proper delivery of planned quantity of explosives.
- 5.3 Muffling of holes In all the blasts sand bags were placed on the conveyor belts so as to provide additional precaution to restrict flying fragments' movement. It is therefore suggested that this need to be carried out till the restrictions are overcome.
- 5.4 Charging of explosives on the last row of holes In case of more than 3 rows, of blasting on the last row of holes, the quantity of explosive can be reduced by 10 to 15% so as to ensure better stability, reduction in back break, less dressing required before finishing excavation due to less loose overhangs and less overhang areas.,

ADDITIONAL PRECAUTIONS

- **6.0 Maximum charge per delay** currently adopted is ultra safe and well within the blast vibration and frequency range stated in DGMS Standards.
- 6.1 Blast Area Security The mine management strictly follow blasting time and adequate number of guards were posted on all roads leading to the mine. All the machineries need to be parked at safer distances following parking norms of each machinery. Before blasting 'Safety Warning' is done, and all persons evacuated out of the prescribed "Danger Zone".

- 6.2 Recording of blast vibration Follow the instructions of the instrument manufacturer while setting the instrument. Measure the distance of the instrument from the centre of the blast. The instrument need to be properly placed on a firm ground and a place not on the probable flyrock zone.
- 6.3 The engineer concerned must move to the shelter after setting the instrument with proper time lags etc.
- 6.4 Secondary Blasting NEVER ADOPTED in this mine and hydraulic Rock Breakers are being used to break oversize boulders.
- **TRAINING**: Safety awareness and training needs of the blasting crew The mine management held training programs for engineers and statutory persons to deliberate on various aspects of blast design, charging, field management, blast area security, provisions of MMR and Mine Vocational Training Rules 1966, and other guidelines. Blasting crew had adequate knowledge of safety during handling, charging, stemming, priming, tie-line hook up, following the siren etc.
- 8.0 PPE all persons engaged in blasting had been provided PPE and also other essential gadgets like whistle, red flags and hand gloves etc. The same need to be strictly adhered to in all time to come.
- 9.0 Post Blast Observations: blast vibration, frequency, flyrock range, dust generation/quantum, fumes etc are observed. It has been observed that by systematic stemming of holes, having mats/conveyor belts cover dust and flyrock under control.
- 10.0 Impact of blasting on health and safety Use of Shock Tubes(Nonel) had eliminated noise/sound level during blasting due to the technological development in initiation. This also had helped in controlling dust generation and the level of dust during post-blast.

CONCLUSION & RECOMMENDATION

The report presents the details of the blasts designed, monitored and studied using Cartridged explosives, for establishing a blasting pattern and allowable maximum charge per delay and per round based on the ground vibration, air overpressure and other post blast details (like fly rock, muck pile, misfires if any, back break, throw etc).

In view of the successful, safe conclusion of the blasts with cartridged explosives by following norms set in the Permission letter, other guidelines, the mine is fully geared up to hold blasts on regular basis in line with the provisions of CMR 2017 etc.

${\bf Controlled\ blasting\ Compliance\ Status:} -$

	Norms	Comments after conclusion of the scientific study
1.	All the blast design parameters at the blasting site.	Being adopted
2.	Blast which was approved type of explosives.	Only approved type of explosives is used.
3.	Only Delay detonators including Shock tubes(Nonel) or Electronic Delay Detonators to be used (to control ground vibrations and to arrest flyrocks and boulder generations)	Shock tube is used. Both down-the-hole & trunk line.
4.	Monitoring of blasts vis-à-vis blast induced ground vibration level & frequency (Hz). Examining the vibration level (mm/s) & frequency with DGMS standards	Done at regular basis.
5.	Following all terms and conditions as stated in the Permission granted by Director of Mines Safety, Jabalpur vide J.R/Metal/Permission -34 /2016 dated 06 01-2017 (Copy placed at Annexure 2)	Being followed.
6.	Flyrock management, generation and control by proper stemming by assuming proper free face ensuring use of quality and explosives & accessories. There by eliminating MISFIRES. Also old conveyor belts with sand bags are used to cover the holes to eliminate fly rock and dust.	Proved effective to eliminate dust and fly rocks with cover on the holes.
7.	Following approval S-O-P for blasting	Being followed in line with Safety Management Plan and Guidelines of DGMS.
8.	Minimum generation of boulders thereby eliminating secondary blasting. However secondary blasting need to be replaced by use of Hydraulic Rock breakers only be replaced by use of Hydraulic Rock Breakers only.	Only Hydraulic Breakers used in case of oversize boulders.
9.	Complained free or less complaints from nearby habitants	There have been no complaints from the distant villagers and habitants.
10.	Only during the day time and the blasting time should be prominently displayed in the area.	Being followed.
11.	Every mine should draw plans to have mitigative measures as per recommendations of the scientific study and provisions of statutory authorities or MMR 1961 or DGMS Guidelines.	Being followed while conducting any blast.

Dr G.K.Pradhan

Professor of Mining Engineering & Dean

Faculty of Engineering & Technology



MicL at 13:33:45 December 4, 2018 Geo: 0.900 mm/s, Mic: 2.000 pa.(L) Geo: 254.0 mm/s Trigger Source

Range Record Time 5.0 sec at 1024 sps Operator/Setup: Operator/SSB.mmb

Notes Location Client:

User Name: PRISM JOHNSON LIMITED

General:

Extended Notes
BANDARKHA LIMESTONE MINE

Microphone Linear Weighting PSPL 4.437 pa.(L) at 0.301 sec

ZC Freq 4.2 Hz

Channel Test Passed (Freq = 19.7 Hz Amp = 1334 mv)

	Tran	Vert	Long	
PPV	0.102	0.102	0.039	mm/s
PPV (Ponderated)	0.026	0.021	0.029	mm/s
PPV	31.21	31.21	22.91	dB
ZC Freq	N/A	N/A	>100	Hz
Time (Rel. to Trig)	-0.112	2.543	1.130	sec
Peak Acceleration	0.005	0.005	0.005	g
Peak Displacement	0.000	0.000	0.000	mm
Sensor Check	Passed	Passed	Passed	
Frequency	7.3	7.7	7.3	Hz
Overswing Ratio	3.6	3.5	3.7	

Peak Vector Sum 0.126 mm/s at -0.112 sec

N/A: Not Applicable


Serial Number UM8131 V 10-76 Micromate ISEE

Battery Level 3.8 Volts

Unit Calibration September 6, 2016 by UES New Delhi File Name UM8131_20181204133345.IDFW


Post Event Notes Bandarkha/1st Bench (L/S), No of holes 20 nos, Depth - 5.0 Mtrs. Charge/delay - 16.25 Kg/delay, Obsevation Distance - 160 mts

DGMS India (A)



a)Industrial Buildings b)Domestic houses/structures

Tran: + Vert: x Long: 0



Time scale has been modified and may not represent the actual length of the event record Time Scale: 0.20 sec/div Amplitude Scale: Geo: 2.000 mm/s/div Mic: 1.000 ps.(L)/div

Sensor Check

Printed: February 8, 2022 (V 10.72 - 10.72)

Format @ 1995-2014 Xmark Corporation



Date/Time Tran at 13:41:35 December 31, 2018 Trigger Source Geo: 0.900 mm/s, Mic: 2.000 pa.(L)

 Range
 Geo: 254.0 mm/s

 Record Time
 5.0 sec at 1024 sps

 Operator/Setup:
 Operator/SSB.mmb

Notes Location: Client:

User Name: PRISM JOHNSON LIMITED

General:

Extended Notes

BANDARKHA LIMESTONE MINE

Microphone Linear Weighting PSPL 15.69 ps.(L) at 0.597 sec

ZC Freq 23 Hz

Channel Test Passed (Freq = 19.7 Hz Amp = 1307 mv)

	Tran	Vert	Long	
PPV	2.396	1.624	2.262	mm/s
PPV (Ponderated)	2.012	1.506	1.745	mm/s
PPV	58.59	55.21	58.09	dB
ZC Freq	26	24	37	Hz
Time (Rel. to Trig)	0.359	0.250	0.317	sec
Peak Acceleration	0.056	0.043	0.054	9
Peak Displacement	0.043	0.011	0.012	mm
Sensor Check	Passed	Passed	Passed	
Frequency	7.3	7.7	7.3	Hz
Overswing Patie	28	24	27	

Peak Vector Sum 2.520 mm/s at 0.358 sec


Serial Number UM8131 V 10-76 Micromate ISEE Battery Level 3.8 Volts

Unit Calibration February 26, 2018 by UES New Delhi
File Name UM8131_20181231134135.IDFW

Post Event Notes


Bandarkha/1st Bench (L/S), No of holes 27 nos, Depth - 6.0 Mtrs. Charge/delay - 27.77 Kg/delay, Obsevation Distance - 160 mts

DGMS India (A)



a)Industrial Buildings b)Domestic houses/structures

Sensor Check



Printed: February 3, 2022 (V 10.72 - 10.72)

Format @ 1995-2014 Xmark Corporation

Time Scale: 0.20 sec/div Amplitude Scale: Geo: 2.000 mm/s/div Mic: 5.000 pa.(L)/div



Long at 13:41:18 March 1, 2019 Trigger Source Geo: 0.900 mm/s, Mic: 2.000 pa.(L) Geo: 254.0 mm/s

Range 5.0 sec at 1024 sps Record Time Operator/Setup: Operator/SSB.MMB

Notes Client:

User Name: PRISM JOHNSON LIMITED

Extended Notes
BANDARKHA LIMESTONE MINE

Microphone Linear Weighting
PSPL 6.237 pa.(L) at 0.365 sec

ZC Freq 15 Hz

Channel Test Passed (Freq = 19.7 Hz Amp = 1334 mv)

	Tran	Vert	Long	
PPV	0.780	0.867	1.387	mm/s
PPV (Ponderated)	0.700	0.741	1.348	mm/s
PPV	48.85	49.76	53.84	dB
ZC Freq	18	28	19	Hz
Time (Rel. to Trig)	0.144	0.069	0.148	sec
Peak Acceleration	0.026	0.021	0.036	9
Peak Displacement	0.022	0.015	0.011	mm
Sensor Check	Passed	Passed	Passed	
Frequency	7.3	7.7	6.9	Hz
Overswing Ratio	3.6	3.4	3.7	

Peak Vector Sum 1.540 mm/s at 0.146 sec


Serial Number UM8131 V 10-76 Micromate ISEE

Battery Level 3.8 Volts

Unit Calibration February 26, 2018 by UES New Delhi
File Name UM8131_20190301134118.IDFW

Post Event Notes Bandarkha/1st Bench (L/S), No of holes 37 nos, Depth - 6.0 Mtrs. Charge/delay - 19.59 Kg/delay, Obsevation Distance - 160 mts


DGMS India (A)



Tran: + Vert: x Long: 0

a)Industrial Buildings b)Domestic houses/structures

Sensor Check



Printed: February 3, 2022 (V 10.72 - 10.72)

Format @ 1995-2014 Xmark Corporation

Time Scale: 0.20 sec/div Amplitude Scale: Geo: 2.000 mm/s/div Mic: 2.000 pa.(L)/div



Tran at 13:38:21 March 5, 2019 Trigger Source Geo: 0.500 mm/s, Mic: 2.000 pa.(L) Geo: 254.0 mm/s

Range

10.749 sec (Auto=10Sec) at 1024 sps Record Time

Operator/Setup: Operator/SSB.MMB

Notes Client:

User Name: PRISM JOHNSON LIMITED

Extended Notes
BANDARKHA LIMESTONE MINE

Microphone Linear Weighting
PSPL 7.013 pa.(L) at 0.421 sec

ZC Freq 15 Hz

Channel Test Passed (Freq = 19.7 Hz Amp = 1307 mv)

	Tran	Vert	Long	
PPV	1.466	1.206	1.277	mm/s
PPV (Ponderated)	1.372	1.055	1.249	mm/s
PPV	54.32	52.63	53.12	dB
ZC Freq	19	26	22	Hz
Time (Rel. to Trig)	0.031	0.068	0.051	sec
Peak Acceleration	0.039	0.023	0.050	9
Peak Displacement	0.093	0.061	0.040	mm
Sensor Check	Passed	Passed	Passed	
Frequency	7.3	7.7	6.9	Hz
Overswing Ratio	3.5	3.4	3.6	

Peak Vector Sum 1.927 mm/s at 0.051 sec


Serial Number UM8131 V 10-76 Micromate ISEE

Battery Level 3.8 Volts


Unit Calibration February 26, 2018 by UES New Delhi
File Name UM8131_20190305133821.IDFW

Post Event Notes Bandarkha/1st Bench (L/S), No of holes 64 nos, Depth - 6.0 Mtrs. Charge/delay - 20.70 Kg/delay, Obsevation Distance - 160 mts

DGMS India (A)



a)Industrial Buildings



Printed: February 3, 2022 (V 10.72 - 10.72)

Format @ 1995-2014 Xmark Corporation



Long at 13:39:47 March 11, 2019

Trigger Source Geo: 0.500 mm/s, Mic: 2.000 pa.(L) Geo: 254.0 mm/s Range

19.0 sec (Auto=10Sec) at 1024 sps Record Time

Operator/Setup: Operator/SSB.MMB

Notes Client:

User Name: PRISM JOHNSON LIMITED

Extended Notes
BANDARKHA LIMESTONE MINE

Microphone Linear Weighting
PSPL 8.177 pa.(L) at 1.561 sec

ZC Freq 12 Hz

Channel Test Passed (Freq = 19.7 Hz Amp = 1332 mv)

	Tran	Vert	Long	
PPV	1.829	0.875	1.797	mm/s
PPV (Ponderated)	1.785	0.700	1.345	mm/s
PPV	56.24	49.84	56.09	dB
ZC Freq	20	24	51	Hz
Time (Rel. to Trig)	0.335	0.215	0.311	sec
Peak Acceleration	0.029	0.026	0.060	9
Peak Displacement	0.116	0.101	0.077	mm
Sensor Check	Passed	Passed	Passed	
Frequency	7.3	7.7	7.1	Hz
Overswing Ratio	3.5	3.4	3.6	

Peak Vector Sum 2.136 mm/s at 0.336 sec


Serial Number UM8131 V 10-76 Micromate ISEE

Battery Level 3.6 Volts

Unit Calibration February 26, 2018 by UES New Delhi File Name UM8131_20190311133947.IDFW

Post Event Notes Bandarkha/1st Bench (L/S), No of holes 78 nos, Depth - 8.0 Mtrs. Charge/delay - 20.97 Kg/delay, Obsevation Distance - 300 mts






Tran: + Vert: x Long: €

a)Industrial Buildings b)Domestic houses/structures

Sensor Check



Printed: February 8, 2022 (V 10.72 - 10.72)

Format @ 1995-2014 Xmark Corporation

Time Scale: 0.20 sec/div Amplitude Scale: Geo: 2.000 mm/s/div Mic: 2.000 ps.(L)/div

पंजीकृत डाक द्वार



भारत सरकार / Govt. of India श्रम एवं रोजगार मंत्रालय / Ministry of Labour & Employment खान सुरक्षा महा—निदेशालय Directorate-General of Mines Safety जबलपुर—क्षेत्र / Jabalpur Region



प्लाट न. 1936 से 1949, जे. डी. ए. स्कीम न. 5, जॉय हायर सेकेन्डरी स्कूल के पिछे, विजय नगर, जबलपुर (म.प्र.) 482 002 फोन : कार्यालय – 0761 2640365, फेक्स – 0761 2640414

संख्या : ज.क्षे. / मेटल / अनुमति—34/2016 / 🗍 📜

/ जबलपुर, दिनांक

6/1/17

प्रेषक:

निदेशक खान सुरक्षा जबल्युर क्षेत्र

सेवा में

अभिकर्ता, बंदर्खा चुनापत्थर खान, मेसर्स प्रिज्म सीमेंट लिमिटेड, राजदीप, रीवा रोड, जिलाः सतना (म प्र) 485 001

विषयः Relaxation from the provisions of Regulation 106(2)(b) of the Metalliferous Mines Regulations, 1961, to work the mine by system of deep hole blasting and deployment of Heavy Earth Moving Machineries at Bandarkha Limestone Mine of M/s Prism Cement Limited.

महोदय.

Please refer to your application vide letter No. MIN/2016-17/BDR/007 dated 23.08.2016 and subsequent correspondence resting with your letter No. MIN/2016-17/BDR/010 dated 15.10.2016 and the plan and enclosures enclosed therewith, on the above subject.

The matter has since been examined in this Directorate on the basis of information furnished and also shown on the plan enclosed therewith.

In exercise of the powers conferred on the Chief Inspector of Mines (also designated as Director General of Mines Safety) under Regulation106(2)(b) of the Metalliferous Mines Regulations, 1961 and by virtue of the authorization granted to me by the Chief Inspector of Mines (also designated as Director General of Mines Safety) under Section 6(1) of the Mines Act, 1952, I hereby grant you relaxation from the provisions of Regulation 106(2)(b) of the Metalliferous Mines Regulations, 1961, to work the mine by system of deep hole blasting and deployment of Heavy Earth Moving Machineries at Bandarkha Limestone Mine of M/s Prism Cement Limited, as shown in red dotted colour line bounded by A-B-C-D-E-F-G-H-I-J-K-L-M-N-O-P-Q-R-S-T-U-V-W-X-Y-Z-A on plan No. PCL/B/2016/102 dated 16.08.2016 enclosed with the application, subject to the following conditions being strictly complied with:

1.0 Except where otherwise provided for in this conditional permission, all provisions of the Metalliferous Mines Regulations, 1961, relating to opencast workings, use of explosives and machinery, etc., shall be strictly complied with.

<1712/2/10)

Page 3

- (5) No road shall have a gradient more than 1 in 16. Ramps with 1 in 10 gradients should not be more that 10m at one stretch and permissions shall be obtained from Directorate.
- (6) Where any road existing above level of surrounding area it shall be provided with strong parapet wall/embankment of following dimensions.
 - Width at top-not less than 1 m.
 - ii. Width at bottom-not less than 2.5m.
 - The height not less that the diameter of tyre of largest vehicle playing on road.

It may be noted that just dumping of mud or Overburden shall not treated as strong parapet wall.

- (7) The portion of the surface haul road in the mine premises where there is heavy traffic of men and machines shall be provided with a separate lane properly fenced off from the haul road for pedestrian, two wheelers and light vehicles.
- 6.0 Precautions-while drilling.
- (1) The position of every deep hole to be drilled shall be distinctly marked by the Mine Foreman so as to be readily seen by the drillers.
- (2) (a) No drilling shall be commenced in an area where shots have been fired, until the blaster has made a thorough examination at all places, including remaining sockets of old deep holes, for unexploded charges that the drill may strike.
 - (b) No drill or bore rod or pick shall be inserted in sockets of old deep holes even if an examination under Clause (a) has failed to reveal presence of explosives.
- (3) No person shall be permitted to remain within a radius of 20 m or within 60 m on the same bench where charging of holes with explosives is being carried out.
- 7.0 Transport of Explosives: Where explosives are transported in bulk for deep hole blasting the following precautions shall be taken:
- (1) Transport of explosives from the magazine to the priming station or the site of blasting shall not be done except in the original wooden or cardboard packing cases. The quantity of explosive transported at one time to the site of blasting shall not exceed the actual quantity required for use in one round of shots. The explosives shall be transported to the site of blasting not more than 90 minutes before the commencement of charging of the holes.
- (2) (a) No mechanically propelled vehicle shall be used for the transport of explosives unless it is of a type approved in writing by the Chief Inspector provided that a Jeep or Land Rover may be used for the transport of detonators from magazines to 'priming stations' subject to the following conditions:
 - (i) Not more than 200 detonators are transported in a vehicle at a time:
 - (ii) The detonators are packed suitably in a wooden box
 - (iii) The wooden box containing detonators is placed inside an outer metal case of construction approved by the Chief Inspector;
 - (iv) The outer metal case shall be suitably bolted to the floor of the vehicle or otherwise fixed in a wooden frame so that the container does not move about

<1712/2/11/de

- while the vehicle is in motion; and
- (v) No person shall ride on the rear portion of the vehicle.
- (vi) Every vehicle used for the transport of explosive shall be marked or placarded on both sides and ends with the word "Explosives" in white letters not less than 15 centimeters high on a red background.
- (vii) Every mechanically propelled vehicle transporting/explosives shall be provided with not less than two fire extinguishers (one of carbon tetrachloride type for petroleum fire and the other of carbon dioxide under pressure type for electrical fire) suitably placed for convenient use.
- (3) (a) The vehicle used for the transport of explosives shall not be overloaded and in no case shall the explosive cases be piled higher than the sides of its body.
 - (b) Explosives and detonators shall not be transported in the same vehicle, at the same time.
- (4) (a) No person other than the driver and his helper (not below 18 years of age) shall ride on a mechanically propelled vehicle used for the transport of explosives.
 - (b) A vehicle loaded with explosive shall not be left unattended.
 - (c) The engine of a vehicle transporting explosives shall be stopped and the brakes set securely before it is unloaded or left standing.
 - (d) A vehicle transporting explosives shall not be driven at a speed exceeding 25 kilometers per hour.
 - (e) A vehicle loaded with explosives shall not be taken into garage or repair shop and shall not be parked in a congested place.
 - (f) A vehicle transporting explosives shall not be refueled except in emergencies and then only when its engine is stopped and other precautions taken to prevent accidents.
 - (g) No trailer shall be attached to a vehicle transporting explosives.
- (5) (a) Every vehicle used for the transport of explosives shall be carefully inspected once in every 24 hours by a competent persons to ensure that:
 - (i) Fire extinguishers are filled and in place;
 - (ii) The electric wiring is well-insulated and firmly secured;
 - (iii) The chassis, engine and body are clean and free from surplus oil and grease;
 - (iv) The fuel tank and feed lines are not leaking; and
 - (v) Lights, brakes and steering mechanism are in good working order.
 - (b) All report of every inspection made under sub-clause (a) shall be signed and dated by competent person making the inspection.
- (6) All operations connected with the transport of explosives shall be conducted under the personal supervision of a foreman solely placed in charge of blasting operations under overall charge of a Asstt. Manager at the mine.
- (7) The blaster shall personally search every person engaged in the transport and use of explosives and shall satisfy himself that no person so engaged has in his possession any cigarette, 'biri' or other smoking apparatus, or any match or any other apparatus of any kind capable of producing a light, flame or spark.

8.0 Precautions during shot-firing:

(1) (a) Shots shall not be fired except during the hours of day-light. All holes charged on any one day shall be fired on the same day.

Page 5

- (b) As far as practicable the blasting shall be carried out either between shifts or during the rest interval or at the end of work for the day.
- (2) During the approach and progress of an electric storm, the following precautions shall be taken:-
 - (a) No explosive, particularly detonators shall be handled.
 - (b) If charging operations have begun, the work shall be discontinued until the storm has passed.
 - (c) If the blast is to be fired electrically all exposed wires shall be coiled up and if possible placed in the mouth of the holes, or kept covered by something other than a metal plate.
 - (d) All wires shall be removed from contact with the steel rails of a haulage track so as to prevent the charge being exploded prematurely by a local strike of the lightening.
- (3) Blasting operation in the mine shall be placed under the charge of an Assistant manager and no blasting shall be done in the mine in the absence of the Assistant Manager.
- (4) No deep hole blasting shall be undertaken within 300m of the any structure not belonging to owner unless permission in writing is obtained from this Directorate as required under the provision of Reg. 164 of MMR, 1961.

Deotale Diagnostic Centre 1868 Diagnostics Health Check-Ups Immunization.

Consultation

Clinic: Vinayak Apt. 3rd floor Dhantoli Lokmat Chouk Nagpur For any assistance call at . 9860204241, 0712-2424868

Email ID: deotaledeepak19577@gmail.com

MEDICAL CHECK-UP REPORT

SR NO.	112
Certificate No	121
EMP CODE	103728
Work Station / Grade	Bandarkha
Designation	Mines Mgr
MOB NO	9109171029
CHECK-UP DATE	11-12-24

EMPLOYEES NAM	AE: Santosh Kun	ar Chaudha	ri Late l	RamKhelawa	n Chaudhari		
Gender: MALE	Age	48 Yrs	Ht:	172 cms	BMI:	22.65	Wt: 67 Kg
Company Addre	MANKAHAR	I,PO: BATHL	A, TEHS	Service of the servic			NA,PIN:485111 (M.P.)
Personal H/O: ALCOHOL: NO		TA	TABACCO: NO		SMOKING: NO		
General Exam:-	Healtl	ıy	BP .:	122/82 m	mHg		: 78 mm/hr
C.V.S.: N R/S: N		V	CNS :N		SP/LIVER:N/P		ER:N/P

Abdomen: soft

DD TEST			PARTITION AND THE PARTITION AN			1 COMMUNICATION STREET, STREET	
st			Result			Normal Range	
ood Sugar			mg/dl			70-160 mg/dl	
moglobin			12.8 gm/dl			12.5 to 16.5 gm/dl	
tal Leukocyte Count			9600 Cumm			4000-11000 /Cumm	
utrophils			78 %			40-80 %	
mphocyte			19 %			20-40 %	
sinophils			2 %			1-6 %	
nocytes			1 %			2-10 %	
R			7 mm/hr			< 20 mm/hr	
olesterol			183 mg/dl			< 220 mg/dl	
glycerides			162 mg/dl			> 200 mg/dl	
L			49 mg/dl			35 TO 50 mg/dl	
L			101.6 mg/dl				
DL			32.4 mg/dl				
O/HDL Ratio:			3.7				
ea			30 mg/dl			10-50	
eatinine			0.8 mg/dl			0.8-1.3	
PT			29 U/L			0-40	
OT			22 U/L			0-40	
TUM AFB		NEGATIVE					
JOL		NEGATIVE					
our Blindness		NO				1	
G		WNL					
tay		WNL		Spirom		WNL	
DIOMETRY		RT: WNL		L	F. WNL		
ion:	Jnaided - Dis	t. Rt - 6/6			Dist. Lf -		
	Unaided - Near Rt - N/6				Near Lf-N/6		
	With Spect Dist. Rt -				With Spect Dist . Lf -		
					With Spect Near . Lf -		
DICAL CHECK - UP:-							
DICAL CHECK - UP:-	Nith Spect Ne				With Spe		

Opinion: He/She is physically & mentally fit . He/She is not suffering from any infectious or contagious diseases

Dr. DEEPAK P. DEOTALE M.B.B.S. A.F.I.H.(Reg. No. 48366)

(See rule 29F (2) and 29L)
Report of medical examination under rule 29B (To be issued in triplicate)

- Certificate No. 121 ... Certified that Shri/Shrimati* Santosh Kuman chaudhau examination. He/she* appears to be years of age.

The findings of the examining authority are given in the attached sheet. It is considered that Shri/Shrimati*... Romfosh. Kumasa. Chaudhasu......

- (a)* is medically fit for any employment in mines.
- (b)* is suffering from..... and is medically unfit for

- (i) any employment in mine; or(ii) any employment below ground; or
- (iii) any employment or work......

(c)* is suffering from..... is should get this disability* cured/controlled and should be again examined within a period ofmonths. He/She will appear for re-examination with the result of test of and the opinion of Specialist from He/She may be permitted/not* permitted to carry on his duties during this period.



Place : PCL Date: 11/12/2024 DR. DEEPAK P. PEOTALE Signature of the examining authority Name and designation in Block letters

* Delete whatever is not applicable. ** One copy of the certificate shall be handed over to the person concerned and another copy shall be sent to the manager of the mine concerned by registered post; and the third copy shall be retained by the examining authority,

Report of the examining authority

(to be filled in for every medical examination whether initial or periodical or reexamination or after cure/control of disability).

Annexure to Certificate No. 121 as result of medical examination on

Identification Mark Male on chest

Left thumb impression of the candidate

General development- Good/Fair/Poor
2. Height
3 Weight6.4 kg.
4 Eyes : (i) Visual acuity-Distant vision (with or without glasses).
Right eye6/9 Left eye6/.9
(ii) any organic disease of eyes √
(iii) night blindness
(iv) Colour blindness
(v) Squint (* to be tested in special cases) Inserted vide notification No.GSR 656 dated 5.6.1980
5 Ears : Hearing : Right ear Left ear
Any organic diseases.
6.Respiratory system. Chest measurement : (i) After full inspirationcms. (ii) After full expirationcms.
7. Circulatory system: (i) Blood Pressure 122/82 (ii) Pulse 7.
8. Abdomen: Tenderness (N
9. Nervous system: History of fits or epilepsy Paralysis Mental health.
10.Locomotory system :
11. Skin. :
12 Hydrocele:
13. Hernia. :
14. Any other abnormality :
15. Urine : Reaction
16. Skiagram of chest. : WNL
17. Any other test considered necessary by the examining authority.: /V O
18. Any opinion of specialist considered necessary.
Signature of the examining authority

Place:

Report of Medical Examination under Mines Rule 29B (To be used in continuation with Form O)

Certificate No. 121

Name: 59 ntosh kumon chaudhord

Identification Marks: mole on chest

Result of Lung Function Test (Spirometry)

Parameters	Predicted Value	Performed Value	% of Predicted
Forced Vital Capacity (FEV)	03.44	03.17	092
Forced Vital Capacity FEV1	02.74	03.07	112_
FEV 1/ FVC	79.65	96.85	122
Peak Expiratory Flow	08.71	04.73	054

Spirometry Report enclosed.

Signature of the Examination Authority

Report of Medical Examination as per the recommendations of National Safety Conferences in Mines (To be used in continuation with Form O)

Certificate No. 121

Name: 597/108/ Kumay chaudhari

Identification Marks: male on chest-

1. Cardiological Assessment

Auscultation	S1	٨.	Performed Value	% of Predicted
	S ₂	N		
	Additional Sound	No	96.85	122
FEV1/FVC		- 1,0		
Electrocardiograp	oh(12leads) findings		Normal/Abnormal	

Enclosed ECG

2. Neurological Assessment 10

Findings	Normal/Abnormal
Superficial Reflexes	Normae!
Deep Reflexes	
Peripheral Circulation	AINO
Vibrational Syndromes	(V _N)

3. ILO Classification of Chest Radiograph

Profusion of Pneumoconiotic Opacities	Grades	Types
Present /Absent		Committee of the second

Enclosed Chest Radiograph

4. Audiometry Findings:

Condition			
Condution Type	Left Ear		Right Ear
Ear Conduction			
	Normal/Abnormal	1	Normal/Abnormal
Bone Conduction	Normal/Abnormal	-	Normal/Abnormal

Enclosed Audiometry Report

5. Pathological/Microbiological Investigations:

S.No.	Tests	Finding	S
1.	Blood-Tc,Dc,Hb,ESR,Platelets	WNL/Abnormal	
2.	Blood Suger-Fasting & P.P.	WNL/Abnormal	
3.	Lipid Profile	WNL/Abnormal	
4.	Blood Urea, Creatimine	WNL/Abnormal	
5.	Urine Routine	WNL/Abnormal	
6.	Stool Routine	WNL/Abnormal	

Enclosed Investigation Reports

6. Special Tests for Mn Exposure:

			The same of the sa
Beh	avioral Disturbances	Present/Not Present	V
Neurological	Speech Defect	Present/Not Present	1
Disturbances	Tremor	Present/Not Present	v
	Adiadocokinesia	Present/Not Present	1
	Emotional Changes	Present/Not Present	1

Enclosed ECG

7. Any other Special Tests Required:

No

Signature of the Examination Authority Seal

ent: SANTOSH KUMAR CHAUDHARI

.d. By:

red.Eqns: RECORDERS

Date: 11-12-2024 10:39:50


Age : 48 Years Height: 172 Cms

Weight : 67 Kgs ID: PR 121


Gender : Male Smoker : No Eth. Corr: 100


Temp : degrees






This report is not to b





		FVC R	esults				
Parameter		Pred	M.Pre%	Pred	M. Post	%Pred	%Imp
FVC	(L)	03.44	03.17	092			
FEV1	(L)	02.74	03.07	112			
FEV1/FVC	(%)	79.65	96.85	122			
FEF25-75	(L/s)	03.62	03.78	104			
PEFR	(L/s)	08.71	04.73	054			
FIVC	(L)		01.17				
FEV.5	(L)		01.96				
FEV3	(L)	03.33	03.17	095			
PIFR	(L/s)		03.44				
FEF75-85	(L/s)		02.18				
FEF.2-1.2	(L/s)	06.45	03.97	062			
FEF 25%	(L/s)	07.79	04.23	054			
FEF 50%	(L/s)	05.43	03.80	070			
FEF 75%	(L/s)	02.42	02.76	114			
FEV.5/FVC	(8)		61.83				
FEV3/FVC	(%)	96.80	100.00	103			
FET (Sec)			01.27				
ExplTime	(Sec)		00.14				

Pre Medication Report Indicates Early Small Airway Obstruction as FEF 25-75 %Pred or PEFR %Pred < 70 Spirometry within normal limits as (FEV1/FVC) %Pred >95 and FVC%Pred >80.



Consultation Diagnostics Health Check- Up: Immunization. Clinic: Vinayak Apt. 3rd floor Dhantoli Lokmat Chowk Nagpur


(Clinic Reg. No. 699)

For any assistance call at . 9860204241, 0712-6610595

Date: 11-12-24


AUDIOLOGICAL EVALUATION

2. CERTIFICATE NO: 121 1. SR. NO. 112 3. EMPLOYEES NAME : Santosh Kumar Chaudhari Late RamKhelawan Chaudhari 4. Employee Mob No : 9109171029 7. AGE: 48 yrs 6. SEX: MALE 8. ADDRESS: PRISM JOHNSON LIMITED, MANKAHARI, PO: BATHIA, TEHSIL: RAMPUR BAGHELAN, DIST: SATNA, PIN: 485111 (M.P.) RT.: WNL 9. DIAGNOSIS LT.: WNL



TEST FREQUENCY WNL = LEFT EAR : 0 Air O WNL = RIGHT EAR : 0 Y Masking No Response: Audiologists Remarks

> Dr. DEEPAK P. DEOTALE M.B.B.S. A.F.I.H. Reg. No. 48366



DeotaleDiagnosticCentre

Consultation Diagnostics Health Check- Ups Immunization.

Clinic: Vinayak Apt. 3rd floor Dhantoli Lokmat Chouk Nagpur

For any assistance call at . 9860204241, 0712-2424868

Email ID: deotaledeepak19577@gmail.com

Patient Name:	Santosh Kumar Chaudhari Late RamKhelawan Chaudhari
Age:	48 yrs.
Gender:	MALE
Req. Doctor:	
Reg . Number:	9109171029
Collection Date:	11-12-24
Reporting Date :	11-12-24

SPUTUM EXAMINATION

ZEIHL NEELSEN STAIN: AFB Not seen

DR .DEEPAK DEVATALE M.B.B.S A.F.I.H(REG NO.48366)

112

Certificate No.

Emp Code 103728

MAYA HOSPITAL

& RESEARCH INSTITUTE

Add.: Plot .P 78, Opposite State Bank of India , W.I.D.C.

Butibori (Nagpur)

Ph 07103-684885

Deotale Diagnostic Center We Care

Phone No: 0712-2424868 Email Id:deotaledeepak19577@gmail.com	Moh No 9860204241 (Clinic Reg. No. 699)	Clinic: Vinayak Apt. 3" floor Dhantoli,	Certifying Surgeon Reg .No. 48366	(Associated fellow Of industrial health)	M.B.B.S., A.F.I.H.	Dr. Deepak P. Deotale	ConsultationDiagnostics HealthCheck-Ups
Company Name	MOB NO	Check Up Date	Gender	Age		Name	rics Health _ Chec
Company Name: PRISM JOHNSON LIMITED, MANKAHARI,PO: BATHIA, TEHSIL: RAMPUR BAGHELAN, DIST: SATNA,PIN:485111 (M.P.)	9109171029	11-12-24	MALE	48 YRS.	RamKhelawan Chaudhari	Santosh Kumar Chaudhari Late	k-Ups Immunization

SI. No.	CSR Project Name/ Activities Undertaken	Item from the list of activities in Schedule VII of the Act	L	ocation of the Pr	oject	lm	plementatio	n Schedule in crore	during FY 20	24-25	Amount Spent In the Project or Programs	Mode of Implementati on Direct:	Mode of Implementation -	
	Ondertaken	Schedule VII of the Act	Local Area (Yes/No)	State	District	Q1	Q2	Q3	Q4	Total	(Rs. in Crore)	Yes/No	Name	CSR Registration No.
A.	Availability of drinking water Sche	edule VII (i))												
1	Supplied 166 trip Drinking water supply through Water Tanker at Mankahari	Availability of Safe Drinking Water Schedule VII (i)	Yes	Madhya Pradesh	Satna	0.02	0	0	0.01	0.03	0.03	Yes	-	-
2	Drilling of a 300-foot bore well with 1 HP submersible water pump installation at Khambha Baba Mankahari	Availability of Safe Drinking	Yes	Madhya Pradesh	Satna	0	0	0	0	0.00	0.01	Yes	-	-
3	Installation of new Hand pump with bore well at nearby villages Baghai	Availability of Safe Drinking Water Schedule VII (i)	Yes	Madhya Pradesh	Satna	0	0.01	0	0	0.01	0.01	Yes	-	-
4	Installation of new hand pump at Bathiya	Availability of Safe Drinking Water Schedule VII (i)	Yes	Madhya Pradesh	Satna	0	0.01	0	0	0.01	0.01	Yes	-	-
5	Providing of Water Cooler and Water Purifier Machine at Government Higher Secondary School Bamhauri FY 24-25	Availability of Safe Drinking	Yes	Madhya Pradesh	Satna	0	0	0	0	0.00	0.01	Yes	-	-
6	Providing 7680 no's packaged water for safe drinking water distribution at Rampur Baghelan		Yes	Madhya Pradesh	Satna	0	0	0	0	0.00	0.00	Yes		-
7	Drilling of 400 ft. bore well at Mahurachh Turning for availability of drinking water	Availability of Safe Drinking Water Schedule VII (i)	Yes	Madhya Pradesh	Satna	0	0	0	0	0.00	0.00	Yes		-
			Sub Total			0.02	0.02	0.00	0.01	0.05	0.07			
В.	Environment, water Conservation and Promoting renewable energy													
8	Road side plantation with 65 tree guards at Baghai and Medhi	Plantation for Environment Conservation Schedule VII (iv)	Yes	Madhya Pradesh	Satna	0	0.02	0	0	0.02	0.02	Yes	-	-
9	Survival of 53000 saplings at Khamhariya Forest Land plantation	Plantation for Environment Conservation Schedule VII (iv)	Yes	Madhya Pradesh	Satna	0.04	0.03	0.03	0.04	0.14	0.12	Yes	-	-

SI. No.	CSR Project Name/ Activities Undertaken	Item from the list of activities in Schedule VII of the Act		ocation of the Pro	ject	lm	plementatio	n Schedule in crore	during FY 20	Amou Proje	Project or Programs	Mode of mplementati on Direct:	Mode of Implementation - Through Implementing Agency	
	- Chashanan		Local Area (Yes/No)	State	District	Q1	Q2	Q3	Q4	Total	(Rs. in Crore)	Yes/No	Name	CSR Registration No.
10	Survival of 20000 saplings at Chulhi Jamodi Forest Land plantation under CSE/CSR redencification Scheme	Plantation for Environment Conservation Schedule VII (iv)	Yes	Madhya Pradesh	Satna	0.03	0	0	0	0.03	0.03	NO.	Divisional Forest Officer Satna	CSR00033247

SI. No.	CSR Project Name/ Activities Undertaken	Item from the list of activities in Schedule VII of the Act	L	ocation of the Pro	oject	lm	plementatio	n Schedule in crore	during FY 20	24-25	Amount Spent In the Project or Programs	Mode of Implementati on Direct:	Mode of Implementation - Through Implementing i	
	Undertaken	Schedule VII of the Act	Local Area (Yes/No)	State	District	Q1	Q2	Q3	Q4	Total	(Rs. in Crore)	Yes/No	Name	CSR Registration No.
11	Distribution of 5200 Fruit Plants to villagers at Mankahari, Malgaon, Mahurachh, Bahelia Bhat, Baghai, Narsinghpur, Hinauti, Ghunghunchihai, Sajjanpur, Bairiha, Sijahata, Bathiya, Municipal Corporation Rampur Baghelan	Conservation Schedule VI	Yes	Madhya Pradesh	Satna	0	0.01	0	0	0.01	0.01	Yes	-	-
12	Desilting of 145 M waterways channel at Bamhauri	Conservation of Natural Resources Schedule VII (iv)	Yes	Madhya Pradesh	Satna	0.01	0.02	0	0	0.03	0.02	Yes	-	-
13	Construction of a Single Bore shaft water harvesting structures at Selhana Baijanaha		Yes	Madhya Pradesh	Satna	0.01	0	0	0	0.01	0.01	Yes	-	-
14	Construction of a Single Bore shaft water harvesting structures at Padkhuri	Water Conservation Schedule VII (iv)	Yes	Madhya Pradesh	Satna	0	0.02	0	0	0.02	0.02	Yes	-	-
15	Construction of 50 perforated drum based water harvesting structures at Tapa	Water Conservation Schedule VII (iv)	Yes	Madhya Pradesh	Satna	0	0.02	0	0	0.02	0.03	Yes	-	-
16	Construction of 50 perforated drum based water harvesting structures at Bairiha		Yes	Madhya Pradesh	Satna	0	0.02	0	0	0.02	0.03	Yes	-	-
17	Construction of 50 perforated drum based water harvesting structures at Bathiya	Water Conservation Schedule VII (iv)	Yes	Madhya Pradesh	Satna	0	0.03	0	0	0.03	0.03	Yes	-	-
			Sub Total			0.09	0.17	0.03	0.04	0.33	0.32			
C.	Health & Hygiene Schedule VII (i)													
18	Free consultation & medicine distribution to 16435 patients from Apr to Mar 25 at PCL Medical Centre Out door patient to nearby villagers from Mankahari, Hinauta, Hinauti, Pithaipur, Badarakha, Sijahata, Medhi, Jhanjhar, Mugwari, Baghai, Bathiya, Bamhauri, Mahurachh, Narsinghpur, Chulhi, Majhiyar, Bairiha & Chormari	Health & Hygiene Schedule VII (i)	Yes	Madhya Pradesh	Satna	0.01	0.01	0.01	0.01	0.04	0.07	Yes	-	-

SI. No.	CSR Project Name/ Activities Undertaken	Item from the list of activities in Schedule VII of the Act	L	ocation of the Pr	oject	lm	plementatio	n Schedule in crore	during FY 20	24-25	Amount Spent In the Project or Programs	Mode of Implementati on Direct:	Mode of Implementation -	
	Undertaken	Schedule VII of the Act	Local Area (Yes/No)	State	District	Q1	Q2	Q3	Q4	Total	(Rs. in Crore)	Yes/No	Name	CSR Registration No.
19	Providing of free ambulance services to 1027 patients from Apr 24 to Mar 25, from Mankahari, Hinauta, Hinauti, Pithaipur, Badarakha, Sijahata, Medhi, Jhanjhar, Mugwari, Baghai, Bathiya, Bamhauri, Mahurachh, Narsinghpur, Chulhi, Majhiyar, Bairiha & Chormari		Yes	Madhya Pradesh	Satna	0.02	0.02	0.02	0.02	0.08	0.08	Yes	-	
20	Door to Door Health Services to 1486 villagers through Mobile Health Van at Sijahata, Baghai, Malgaon, Narsinghpur, Badarkha, Chulhi and Majhiyar	Health & Hygiene Schedule	Yes	Madhya Pradesh	Satna	0	0	0	0	0.00	0.00	Yes	-	-
21	Organisation of Mega Medical Camps at Katra Narsinghpur (Attended 326 Pts)	Health & Hygiene Schedule VII (i)	Yes	Madhya Pradesh	Satna	0	0	0.02	0.01	0.03	0.01	Yes	-	-
22	Organisation of Mega Medical Camps at Jhanjhar Sijahata (Attended 235 patients		Yes	Madhya Pradesh	Satna	0	0	0	0	0	0.01	Yes	-	-
23	Organisation of Mega Medical Camps at Bairiha (Attended 284 patients)	Health & Hygiene Schedule VII (i)	Yes	Madhya Pradesh	Satna	0	0	0	0	0	0.01	Yes	-	-
24	The organisation of Mega Medical Camps at Malgaon (Attended 235 patients)	Health & Hygiene Schedule VII (i)	Yes	Madhya Pradesh	Satna	0	0	0	0	0	0.01	Yes	-	-
25	Operation & Maintenance of Sulabh Complex at Mahurachh Turning (12 months)		Yes	Madhya Pradesh	Satna	0.00075	0.00075	0.00075	0.00075	0	0.00	Yes	-	-
26	Providing 03 sanitary pad vending machines at Govt High School Bamhauri, Bairiha and Sijahata villages	Health & Hygiene Schedule	Yes	Madhya Pradesh	Satna	0	0.01	0	0	0.01	0.00	Yes	-	-
			Sub Total			0.03	0.04	0.05	0.04	0.16	0.19			
D.	Promoting Education Schedule V	II (ii)												
27	Renovation of Government Middle School Chulhi	Promoting Education Schedule VII (ii)	Yes	Madhya Pradesh	Satna	0	0.01	0.02	0	0.03	0.04	Yes	-	-

SI. No.	CSR Project Name/ Activities Undertaken	Item from the list of activities in Schedule VII of the Act	L	ocation of the Pr	oject	lm	plementatio	n Schedule in crore	during FY 20	24-25	Amount Spent In the Project or Programs	Mode of Implementati on Direct:		
	Undertaken	Schedule VII of the Act	Local Area (Yes/No)	State	District	Q1	Q2	Q3	Q4	Total	(Rs. in Crore)	Yes/No	Name	CSR Registration No.
28	Painting of Government Degree College Rampur Baghelan	Promoting Education Schedule VII (ii)	Yes	Madhya Pradesh	Satna	0	0.01	0.01	0	0.02	0.02	Yes	-	-
29	Renovation of Government Primary School Bardadih	Promoting Education Schedule VII (ii)	Yes	Madhya Pradesh	Satna	0	0	0.01	0.01	0.02	0.02	Yes	-	-
30	Construction of 58 M Boundary wall at Government Primary School Medhi	Promoting Education Schedule VII (ii)	Yes	Madhya Pradesh	Satna	0.03	0.03	0.02	0.04	0.12	0.04	Yes	-	-
31	Renovation and support to Anganvadi-1 at Bamhauri village	Promoting Education Schedule VII (ii)	Yes	Madhya Pradesh	Satna	0	0	0.01	0.01	0.02	0.03	Yes	-	-
32	200 Awareness Wall paintings and slogans writing pertaining to different social themes at Mahurachh, Karmau, Bairiha and Tapa	Promoting Education	Yes	Madhya Pradesh	Satna	0.01	0	0	0	0.01	0.01	Yes	-	-
	Distribution of stationery and Bag to 800 students from Govt Schools Hinauti, Sijahata, Medhi, Bamhauri, Chulhi, Malgaon, Majhiyar, Mankahari, Narsinghpur and Baghai	Promoting Education Schedule VII (ii)	Yes	Madhya Pradesh	Satna	0	0.01	0.01	0	0.02	0.03	Yes	-	-
34	Scholarship to 36 Meritorious (1st, 2nd and 3rd rank holder) Students from Government Higher Secondary School Sijahata and Bamhauri, Government Girls Middle School Sijahata, Government Middle School Mankahari, Hinauti, Baghai, Malgaon and Chulhi	Promoting Education	Yes	Madhya Pradesh	Satna	0	0.01	0	0	0.01	0.01	Yes	-	-
			Sub Total			0.04	0.07	0.08	0.06	0.25	0.20			
E.	Rural Infrastructure Development	Schedule VII (X)												
35	Construction of 135 meters Pathway along with pond at Mankahari		Yes	Madhya Pradesh	Satna	0	0.01	0.02	0	0.03	0.04	Yes	-	-
36	Construction of 100 running meter drainage at Chulhi	Rural Infrastructure Development Schedule VII (X)	Yes	Madhya Pradesh	Satna	0	0.02	0.02	0	0.04	0.03	Yes	-	-
37	Construction of 100 running meter drainage at Baghai	Rural Infrastructure Development Schedule VII (X)	Yes	Madhya Pradesh	Satna	0	0.02	0.02	0	0.04	0.03	Yes	-	-

SI. No.	CSR Project Name/ Activities Undertaken		L	ocation of the Pr	oject	lm	plementatio	n Schedule in crore	during FY 20	24-25	Amount Spent In the Project or Programs	Mode of Implementati on Direct:	Mode of Implementation - Through Implementing Agency	
	Undertaken		Local Area (Yes/No)	State	District	Q1	Q2	Q3	Q4	Total	(Rs. in Crore)	Yes/No	Name	CSR Registration No.
	Repairing and renewal of the Vindhya Club Community building badminton court flooring at Satna 24-25			Madhya Pradesh	Satna	0.01	0.01	0	0	0.02	0.02	Yes	-	-
39	Construction of river ghat near devimandir at Hinauti	Rural Infrastructure Development Schedule VII (X)		Madhya Pradesh	Satna	0	0.02	0.02	0	0.04	0.04	Yes	-	-
40	Repairing and renewal of the Cremation shed at Malgaon 24-25	Rural Infrastructure Development Schedule VII (X)		Madhya Pradesh	Satna	0	0	0	0	0.00	0.00	Yes	-	-
			Sub Total			0.01	0.08	0.08	0.00	0.17	0.16			
F.	Social Welfare Schedule VII (iii, iv	& vi)												
	Support to Old Age Home, Dr. Lalta Prasad Khare Charitable Trust, Nimi Babupur	Social Welfare Schedule VII (iii)	Yes	Madhya Pradesh	Satna	0.02	0.02	0.01	0.01	0.06	0.06	No	Dr. Lalta Prasad Khare Public Charitable Trust Chandrashaya Sakariya Road Nimi Satna	CSR00000455
42	Distribution of thermo cot innerwear to 200 Sr. Citizens at Satna FY 24- 25	Facilities for Senior Citizen Schedule VII (iii)	Yes	Madhya Pradesh	Satna	0	0	0	0	0.00	0.01	Yes	-	-
43	Assistance for Armed Forces Flag Day	Assistance Measures for development of societies, war widows, social weaker section of society, promoting art and culture Schedule VII (iii)	Yes	Madhya Pradesh	Satna	0	0	0.01	0	0.01	0.01	Yes	-	-
44	Distribution of 400 T-shirts to Women from Rewa under "Empowering Women" at Rewa	"Empowering Women" Schedule VII (iii) FY 24-25, Social welfare	Yes	Madhya Pradesh	Rewa	0	0	0	0	0.00	0.00	Yes	-	-
45	Fodder arrangement for 100 cows at Gaushala Mahurachh	Animal Welfare Schedule VII (iv)	Yes	Madhya Pradesh	Satna	0.02	0.01	0	0	0.03	0.03	Yes	Jai Gurudev Group Of Social Welfare Organisation Nagod	CSR00015295

SI. No.	CSR Project Name/ Activities Undertaken	Item from the list of activities in Schedule VII of the Act	L	ocation of the Pro	oject	lm	plementatio	n Schedule in crore	during FY 20	24-25	Amount Spent In the Project or Programs	Mode of Implementati on Direct:	Mode of Implementation -	
	Undertaken	Schedule VII of the Act	Local Area (Yes/No)	State	District	Q1	Q2	Q3	Q4	Total	(Rs. in Crore)	Yes/No	Name	CSR Registration No.
46	Assistance to Govansh Vikash Aum Anushandhan Kendra, Deendayal Research Institute, Chitrakoot FY 24-25	Animal Welfare Schedule VII (iv)	Yes	Madhya Pradesh	Satna	0	0	0	0	0.00	0.05	No	Deen Dayal Research Institute, 7-E, Swami Ramtirth Nagar, Rani Jhansi Road, New Delhi, DL01, DL, 110055 Tel.: 07670-265623, email: drichitrakoot.org.in, info@dri.org.in Website: www.dri.org.in	CSR00008614
			Sub Total			0.04	0.03	0.02	0.01	0.10	0.16			
G.	Vocational Skill Development Sch	nedule VII (ii)												
	Training program for driver with license making for 50 persons from Rampur Baghelan Block		Yes	Madhya Pradesh	Satna	0	0	0.01	0	0.01	0.01	Yes	-	-
48	Training program for Stitching for 33 persons from nearby villages. (Sijahata (15) and Baghai (18))	Vocational Skill Development Schedule VII (ii)	Yes	Madhya Pradesh	Satna	0	0	0.02	0.01	0.03	0.04	Yes	Pipra Sewa Dal Biradari Sansthan, Gram Pipra Kala, Post Maihar, Satna	CSR00067053
49	Training program for farmers for organic farming to 50 farmers from Baghai, Sijahata, Hinauti, Bathiya, Bairiha, Mahurachh, Malgaon, Narsinghpur	Livelihood Assistance Schedule VII (ii)	Yes	Madhya Pradesh	Satna	0	0	0.01	0	0.01	0.01	Yes	Pipra Sewa Dal Biradari Sansthan, Gram Pipra Kala, Post Maihar, Satna	CSR00067053
			Sub Total			0.00	0.00	0.04	0.01	0.05	0.06			
			Grand Total			0.23	0.41	0.30	0.17	1.11	1.16			



PRISM CEMENT LIMITED

Works: Vill-Mankahari, P.O.-Bathia, Dist.-Satna - 485111 (M.P.) India Tel.: (07672) 275301-2, 275621-22, Fax: 275303 Corsp. Add.: 'Rajdeep', Rewa Road, Satna - 485 001 (M.P.) India Tel.: (07672) 402726, Fax: 402710



दिनांक: 01.04.2013

प्रति,

सरपंच महोदय ग्राम-पंचायत-हिनौती, विकास खण्ड-रामपुर बाघेलान जिला-सतना (म०प्र०)

विषयः मौजा बदरखा में प्रिज्म सीमेंट लिमिटेड मनकहरी के लीज पर पर्यावरण अनापत्ति प्रमाण पत्र के संबंध में।

मान्यवर,

सादर निवेदन है कि मध्य प्रदेश शासन के राज्य स्तरीय पर्यावरण प्रभाव निर्धारण प्राधिकरण भोपाल, म0प्र0 द्वारा पत्र क्र0 3080/SEIAA/13 Dated 20.03.2013 के मौजा बदरखा में प्रिज्म सीमेंट लिमिटेड मनकहरी को स्वीकृत माइनिंग लीज रकवां 40.236हेक्टेयर पर राज्य स्तरीय पर्यावरण प्रभाव निर्धारण प्राधिकरण भोपाल, म०प्र० पर्यावरण अनापत्ति प्रमाण पत्र दिया गया है।

अस्तु उपरोक्त जानकारी आपकी ओर सम्प्रेषित है।

संलग्नः पत्र की छायाप्रति संलग्न है।

ज. थै. समपुर वाघेलान, जिला सतना (म.ज.)

वास्ते-प्रिज्म सीमेंट लिमिटेंड



PRISM CEMENT LIMITED

Works: Vill-Mankahari, P.O.-Bathia, Dist.-Satna - 485111 (M.P.) India Tel.: (07672) 275301-2, 275621-22, Fax: 275303 Corsp. Add.: 'Rajdeep', Rewa Road, Satna - 485 001 (M.P.) India Tel.: (07672) 402726, Fax: 402710



दिनांक: 01.04.2013

प्रति,

विकास खण्ड अधिकारी, (अट्ट्र अप्लेपालन कार्यकारी)

विकास खण्ड-रामपुर बाघेलान

जिला-सतना (म०प्र०)

विषयः मौजा बदरखा में प्रिज्म सीमेंट लिमिटेड मनकहरी के लीज पर पर्यावरण अनापत्ति प्रमाण पत्र के संबंध में।

मान्यवर,

सादर निवेदन है कि मध्य प्रदेश शासन के राज्य स्तरीय पर्यावरण प्रभाव निर्धारण प्राधिकरण भोपाल, म0प्र0 द्वारा पत्र क्र0 3080/SEIAA/13 Dated 20.03.2013 के मौजा बदरखा में प्रिज्म सीमेंट लिमिटेड मनकहरी को स्वीकृत माइनिंग लीज रकवां 40.236हेक्टेयर पर राज्य स्तरीय पर्यावरण प्रभाव निर्धारण प्राधिकरण भोपाल, म0प्र0 पर्यावरण अनापत्ति प्रमाण पत्र दिया गया है।

अस्तु उपरोक्त जानकारी आपकी ओर सम्प्रेषित है।

संलग्नः पत्र की छायाप्रति संलग्न है।



1-25-13 Transis san

TO GO GO

आम सूचना

सर्वसाधारण को सूचित किया जाता हैं कि भारत सरकार के वन एवं पर्यावरण मंत्रालय के द्वारा गठित म.प्र. राज्य स्तरीय पर्यावरण प्रभाव निर्धारण प्राधिकरण, भोपाल के आदेश क्रमांक 3080/SEIAA/13,date 20. 03. 2013 市 द्वारा मेसर्स प्रिज्य सीमेन्ट लिमिटेड की 40.236 हैक्टेयर बन्दरखॉ लाइमस्टोन खुलो खदान जिसको उत्पादन क्षमता 2.4Lacs टन/वर्ष, ग्राम बंदरखाँ तहसील रामपुर बांचेलान एवं जिला सतना म.प्र. हेतु पर्यावरणीय स्वीकृति प्रदान कर दी गई हैं। उक्त पर्यावरणीय स्वीकृति आदेश की एक प्रति म.प्र. प्रदूषण नियंत्रण बोर्ड, भोपाल के समक्ष मुरिक्षत हैं तथा उक्त आदेश को म.प्र. राज्य स्तरीय पर्यावरण प्रभाव निर्धारण प्राधिकरण, भोपाल की बेवसाइट www.mpseiaa.nic.in पर भी देखा जा सकता है।

अत: सर्वसाधारण को सूचित हो।

02/04/13



आम सूचना

सर्वसाधारण को सूचित किया जाता है कि भारत सरकार के वन एवं पर्यावरण मंत्रालय के द्वारा गठित म.प्र. राज्य स्तरीय पर्यावरण प्रभाव निर्धारण प्राधिकरण, भोपाल के आदेश क्रमांक 3080/SEIAA/13, date 20.03.2013 के द्वारा मेसर्स प्रिज्म सीमेन्ट लिमिटेड की 40.236 हैक्टेयर बन्दरखाँ लाइमस्टोन खुली खदान जिसकी उत्पादन क्षमता 2.4Lacs टन/वर्ष, ग्राम बंदरखाँ तहसील रामपुर बाघेलान एवं जिला सतना (म.प्र.) हेतु पर्यावरणीय स्वीकृति प्रदान कर दी गई है. उक्त पर्यावरणीय स्वीकृति आदेश की एक प्रति म.प्र. प्रदूषण नियंत्रण बोर्ड, भोपाल के समक्ष सुरक्षित हैं तथा उक्त आदेश को म.प्र. राज्य स्तरीय पर्यावरण प्रभाव निर्धारण प्राधिकरण, भोपाल की बेवसाइट www.mpseiaa.nic.in पर भी देखा जा सकता है. अत: सर्वसाधारण को सूचित हो।

02 04 13

Suggestions received during Public Hearing of 40.236 Ha Badarkha Limestone Mines of M/s Prisn Cement Limited at Govt. Primary Shala, Badarkha Dated 07.07.2012

S. No	Name and Address	Query	Reply
1	Shri Chhatrapati Singh, President, Seva Sahkari Samiti Vill- Sijahata	Agree with project implementation, development of the area will take place, social status of general public of the area will be improved	Thanks for your co-operation, employment will be given according to sligibility & requirement
2	Smt Shanti Kori, Sarpanch, Vill – Hinauti, Dist - Satua	Requested for employment to villagers, plantation, requested the villagers to cooperate the company in establishing the mines	Thanks for your co-operation. Dense plantation will be done in mines periphery, employment will be given according to eligibility & requirement.
3	Shri Jagdish Singh S/O Sukhdov Singh Vill- Badarkha, Distt – Satna	Area will be developed, employment will be given to villagers, no objection in establishing mines	Thanks for your co-operation, employment will be given according to eligibility & requirement
4	Shri Mohit Singh, S/O Shri Ram Charit Singh Vill- Badarkha, Disti – Satus	Area will be developed, employment will be given to villagers	Thanks for your co-operation employment will be given according to eligibility & requirement
5	Shri Rehini Singh, Vill — Badarkha, Distt — Satna	Agree with project implementation, Area will be developed, employment will be given to villagers	Thanks for your co-operation employment will be given according to eligibility & requirement
6	Shri Ganesh Singh, Vill – Badarkha, Distt – Satua	Agree with project implementation, Area will be developed, employment will be given to villagers	Thanks for your co-operation employment will be given according to eligibility & requirement
7	Shri Ramesh Singh, Vill - Badarkha, Distt - Satna	Agree with project implementation, Area will be developed, employment will be given to villagers	Thanks for your co-operation employment will be given according to eligibility & requirement
8	Shri Hari Shankar Tiwari, Vill - Mau, Disti - Rowa	 Noise Pollution due to blasting hearing impairment, mental ill health etc. 	Controlled blasting will be done at per guidelines of IBM, delay detonating technique will be adopted due to which no hearing impairment or mental ill health is possible
		 Air pollution due to Blasting, cement manufacturing process 	Air pollution control devices will be installed at all the point source and have been already installed a various locations (emission points) in plant.
		 Increase of pollutant matter in air 	Wet drilling will be done, water spray on haul roads.
		4- Water pollution due to settling of dust, stone and smoke from air into water body, ground water level will also be affected.	All due care will be made to arrest the dust generated at source ground water level will be improved due to collection of rainy water in abandoned min- pits
		5- Geological problems – all the living being will be scared of vibration caused due to blasting. Mining will be deeper enough due to which earth strata will become weak, release of poisonous gases,	No mining will be done beyond permitted depth assigned by IBM by which no effect is envisaged or earth strata and no possibility of release of poisonous gases earthquake and landslide

- earthquake and landslide may be caused
- 6- Mental problems pollutants released may cause mental ill health, man of an ordinary prudence, thinking ability etc will also be affected.
- Physical problems mining will cause physical problems in 50 km of radius. Progenies will face problems of infertility, handicapped, dwarfness, annoyance, madness etc.
- 8- Problems of Homes- cracks in walls or collapse of buildings within 10-15 years
- Effects on youths & pregnant ladies- development of infants, youths and pregnant ladies will be affected.
- 10- Effects on farmers life of farmers will be ill affected who are tolally dependent on agriculture
- Affection with parental birth place- people who leaves their homes even without their own will

All the pollution control devices will be installed as per guidelines of CPCB/ MPPCB to avoid the release of pollutant. Cause of mental ill health is not possible.

No possibility of any such physical problems

Mining will be done as per guidelines of IBM and ground vibration will be monitored regularly, vibration will not be enough to cause harm to the homes as all the guidelines of IBM will be followed

Not acceptable, no effect on development of infants, youths and pregnant ladies, with the compliance of statutory guidelines

Not acceptable, due to compliance of related guidelines of the Govt., there will be no adverse effect. Life style will be improved.

There is no habitation in the lease area hence the allegation is not acceptable